

product data sheet

TITANEL

Code 1399 Revision 0 13 April 2017

Properties	Test method	Units	Specification	Typical values
Congealing point	ASTM D 938	°C	80 – 85	83
Drop melting point	ASTM D 3954	°C	83 - 93	88
Penetration at 25°C	ASTM D 1321	0.1 mm	4 – 9	7
Kinematic viscosity at 100°C	ASTM D 445	cSt	9 – 11	9.4
Colour	Sasol 2000	Saybolt	20 – 30	+28
Oil content	ASTM D 721	mass %	0.75 max	0.50
Centrifuge test	Sasol 1052		Free from foreign material	Pass
Odour	ASTM D 1833	-	Practically odourless	Pass
Appearance	Sasol 1074	Pass / fail	White	Pass

TITANEL contains no preservatives or antioxidants

INCI: Synthetic Wax

Compliance

FDA: This product complies with the requirements of 21 Code of Federal Regulations: 175.250 (Paraffin, synthetic)

Packaging

TITANEL is supplied in the form of white pastilles packed in 20kg paper bags

Note

To obtain the best performance from the product, we recommend use within 5 years from sample date on the Certificate of Analysis. Product should be stored under standard warehousing conditions, at least in a clean dry place, in its original packing at a temperature not exceeding 35°C.

Notice This product information is indicative and does not include any guarantee

Sasol Chemicals a division of Sasol South Africa (Pty) Ltd.
ISO 9001/ISO 14001