



sasol

PRODUCT DATA SHEET

Base Chemicals

Technical Services and Product Stewardship

MP-Cresol 45 (P40)

Technical support:
Base Chemicals
Technical Services and
Product Stewardship
Sasol Place
50 Katherine Street
Sandton
South Africa

Tel: +27 (0)10 344 5000

Sales office:
Base Chemicals
Industrial Chemicals Division
Sasol Place
50 Katherine Street
Sandton
South Africa

Tel: +27 (0)10 344 5000

Date of issue July 2022

www.sasol.com

MP-Cresol 45 (P40)

Features

- Synonyms: MP45(P40), MPP40
- Appearance: Yellow liquid
- Smell: Phenol-like
- UN number: 2076

Applications

- Used as a solvent for magnet wire enamel coatings. These coatings act as insulators for wires that are wound around the armatures of electric motors.
- Used in the production of laminates for printed circuit boards.
- Other uses include ore flotation, paint strippers, cleaners, soap and disinfectants applications.

Typical properties

TEST	UNITS	TYPICAL VALUE	TEST METHOD
PHENOL	mass%	40	ASTM D5310
O-CRESOL	mass%	0.1	ASTM D5310
MP-CRESOL	mass%	54	ASTM D5310
M-CRESOL	mass%	27	ASTM D5310
2,4/ 2,5-XYLENOLS	mass%	2	ASTM D5310
2,6-XYLENOLS	mass%	1	ASTM D5310
XYLENOLS + ETHYLPHENOLS	mass%	6	ASTM D5310
WATER	mass%	0.3	ASTM D1364; ASTM E203
NEUTRAL OIL	mass%	0.2	ASTM D5310
NITROGEN BASES AS PYRIDINE	ppm	<20	ASTM D4471
SULPHUR	ppm	<50	ASTM D5453
DENSITY AT 20 °C	kg/L	1.048	ASTM D4052
COLOUR	Pt-Co	60	ASTM D1209

Packaging

- Available in bulk, isotainers and 200kg or 225kg nett new galvanised drums.

Base Chemicals

Technical Services and Product Stewardship

MP-Cresol 45 (P40)

Shelf life

- MP-Cresol 45 (P40) is stable if stored and handled according to the recommendations in the Sasol SDS and is expected to retain compliance with test properties to within specification limits.
- Depending upon storage conditions, the product may absorb moisture from the air, darken in colour over time, or leach low level metals from the storage vessel. This will be minimized, however, if the container remains sealed and the product is not exposed to air or excessive heating.
- It is recommended that a sample of the product be tested to confirm compliance to test specifications following prolonged storage, especially under non-ideal storage conditions.

Disclaimer

This information is based on Base Chemicals' current knowledge and experience and is provided in good faith. In view of many factors that may affect processing and application, this data does not relieve processors from the responsibility of carrying out their own tests and experiments; neither does it imply any legally binding assurance of certain properties for a specific purpose. It is the responsibility of those to whom Base Chemicals has supplied their products to ensure that any proprietary rights and existing laws and legislation are observed. It is the responsibility of our customer to determine that the use of our product(s) is safe, lawful and technically suitable in intended applications. Please contact your local sales representative for up-to-date product and specification information. It is strongly urged that the Safety Data Sheet (SDS) be thoroughly reviewed by anyone who will be working with MP-Cresol 45 (P40).