



Sasol Engine Oil Multigrade J4 15W-40 *ENGINE OIL, MULTIGRADE, SAE 15W-40*

Description

Sasol Engine Oil Multigrade J4 15W-40 is a premium heavy duty engine oil formulated to meet the most stringent performance requirements of the API CJ-4 service category for 2007.

Application

Sasol Engine Oil Multigrade J4 15W-40 is intended for all on-and off-highway medium and heavy duty diesel vehicles built prior to 2007 and models built from 2007.

Sasol Engine Oil Multigrade J4 15W-40 is recommended for naturally aspirated, turbocharged or EGR diesel engines and most gasoline engines. This oil is also suitable for many transmissions and other applications requiring high quality engine oils.

Sasol Engine Oil Multigrade J4 15W-40 meets and exceeds the performance requirements of diesel and petrol engine manufacturers.

Features and Benefits

Sasol Engine Oil Multigrade J4 15W-40 has the following features and benefits:

- Meets requirement of diesel particulate filters
- 2007 EPA emission friendly
- Extends oil drain intervals
- Reduces oil thickening and oil consumption
- Effectively reduces engine wear and controls deposits

Product Specifications

ACEA E7-04 Issue & E9-08	MAN 3275
EO-O Premium Plus 07	Mercedes-Benz 228.31
API CJ-4 /CI-4 Plus/SM/CF	JASO DH-2
Cummins CES 20081	Volvo VDS-4
Caterpillar ECF-2, ECF -3	MTU Type 2.1
Renault RLD-3	DDC 93K218



Typical Characteristics

Property	Units	Typical	ASTM	IP
Viscosity			D445	71
@ 100°C	mm ² /s	14		
@ 40°C	mm ² /s	118		
Apparent Viscosity	mPa.s @ -20°C	6510	D5293	
Viscosity Index		139	D2270	226
Pour Point	°C	-30	D97	15
Flash Point (COC)	°C	236	D92	36
Evaporative Loss (Noack)	% m/m	12	CEC L-40-T-87 or DIN 51581	
Density @ 20°C	kg/m ³	867	D4052	365
Sulphated Ash	% m/m	1.0	D874	163
Total Base Number	mg KOH/g	7.6	D2896	276

Storage and Handling

Use PVC, nitrile or other oil resistant gloves and protective clothing to prevent skin contact. Where eye contact is a potential hazard, goggles should be worn.

Avoid temperatures above 80°C and strong oxidizing agents.

Ambient temperatures and atmospheric pressures normally encountered within buildings or roofed-over outdoor storage areas are acceptable. Avoid entering areas where mists or vapours have built up as a result of abnormal temperatures or pressures without the proper breathing equipment and protective clothing.

Pack Information

Product Code	Pack Size
---------------------	------------------