

Prop BH

Version 1.01 Revision Date 08.11.2023

SECTION 1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name Prop BH

Product code 2045

Relevant identified uses of the substance or mixture and uses advised against

Use Solvent.

Uses advised against Prohibited for use in production of hand sanitizer.

Manufacturer or supplier's details

Company Sasol Chemicals, a division of Sasol South Africa Ltd

Address Sasol Place, 50 Katherine Street

Sandton 2090 South Africa

Telephone +27103445000

E-mail address sasolchem.info.sa@sasol.com Supplier's details Sasol Chemicals Pacific Ltd

61 Robinson Road

#17-02 068893 Singapore

Telephone +65 6533 8856 E-mail address info.sg@sasol.com

Emergency Phone Number

Emergency telephone number +44 (0)1235 239 670 (Europe, Israel, Africa, Americas)

+44(0)1235 239 671 (Middle East, Arabic African countries)

+65 3158 1074 (Asia Pacific)

+86 400 120 6011 (China)



Prop BH

Version 1.01 Revision Date 08.11.2023

+27 (0)17 610 4444 (South Africa)

0800 112 890 RSA-Local only

+61 (2) 8014 4558 (Australia)

SECTION 2. Hazards identification

Classification of the substance or mixture

GHS Classification

Notification of the ministry of industry on the system of classification and hazard communication of hazardous substances B.E. 2555 (GHS 2009)

Flammable liquids Category 3

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Specific target organ toxicity - single exposure Category 3

GHS label elements

Classification

Hazard pictograms







Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash skin thoroughly after handling.



Prop BH

Version 1.01 Revision Date 08.11.2023

P280 Wear protective gloves/ eye protection/ face protection. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P332 + P317 If skin irritation occurs: Get medical advice/ attention.

P332 + P317 If skin irritation occurs: Get medical advice/ attention. P305 + P354 + P338 + P317 IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical help.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3. Composition/information on ingredients

HAZARDOUS INGREDIENTS

Propan-1-ol

Contents: $\ge 40.00 - \le 60.00 \% W/W$

CAS-No. 71-23-8 Index-No. 603-003-00-0 EC-No. 200-746-9 Hazard statements *H225 H318 H336 H303 H313*



Prop BH

Version 1.01 Revision Date 08.11.2023

Butan-2-ol

Contents: \geq 20.00 - \leq 40.00 %W/W

CAS-No. 78-92-2 **Index-No.** 603-004-01-3 **EC-No.** 201-158-5

Hazard statements H319 H335 H336 H226

Iso-butanol

Contents: >= 10.00 - <= 25.00 % W/W

CAS-No. 78-83-1 **Index-No.** 603-108-00-1 **EC-No.** 201-148-0

Hazard statements H226 H315 H318 H335 H336

n-Butanol

Contents: < 10.00 %W/W

CAS-No. 71-36-3 Index-No. 603-004-00-6 EC-No. 200-751-6

Hazard statements *H226 H302 H335 H315 H318 H336*

3-Methylbutan-2-ol

Contents: < 4.00 %W/W

CAS-No. 598-75-4 Index-No. 603-006-00-7 EC-No. 209-950-2

Pentan-2-ol

Contents: < 4.00 %W/W

CAS-No. 6032-29-7 **Index-No.** 603-006-00-7 **EC-No.** 227-907-6

Hazard statements H226 H315 H335



Prop BH

Version 1.01 Revision Date 08.11.2023

SECTION 4. First aid measures

Description of necessary first-aid measures

Inhalation Move to fresh air in case of accidental inhalation of vapours. If

breathing is irregular or stopped, administer artificial respiration. Get

medical attention immediately

Skin contact Wash off immediately with soap and plenty of water while removing

all contaminated clothes and shoes. Get medical attention if irritation

develops and persists.

Eye contact Remove contact lenses. Rinse immediately with plenty of water, also

under the eyelids, for at least 5 minutes. Get medical attention

immediately

Ingestion If swallowed, seek medical advice immediately and show this

container or label. Do not induce vomiting without medical advice.

Never give anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed

Refer to SECTION 11

SECTION 5. Firefighting measures

Suitable extinguishing media Water spray, Foam, CO2, Dry powder.

Unsuitable extinguishing

media

Do NOT use water jet.

the substance or mixture

Special hazards arising from Hazardous decomposition products

Special protective equipment Wear self-contained breathing apparatus and protective suit.

for firefighters



Prop BH

Version 1.01 Revision Date 08.11.2023

SECTION 6. Accidental release measures

Personal precautions Use personal protective equipment. Do not breathe vapours or spray

> mist. Ensure adequate ventilation. Keep away from sources of ignition - No smoking. Use non-sparking tools. Shut off all sources of

ignition.

Environmental precautions Avoid subsoil penetration. Do not flush into surface water or sanitary

> sewer system. Should not be released into the environment. Prevent further leakage or spillage if safe to do so. Do not allow material to

contaminate ground water system.

Soak up with inert absorbent material (e.g. sand, silica gel, acid Methods for cleaning up

binder, universal binder, sawdust). The material taken up must be

disposed of in accordance with regulations.

Reference to other sections Refer to Section 8 and 13

SECTION 7. Handling and storage

Safe handling advice Wear personal protective equipment. Avoid contact with skin and

> eyes. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Ensure all equipment is electrically grounded before beginning transfer

operations.

Advice on protection against No data available.

fire and explosion

Requirements for storage areas and containers

Keep containers tightly closed in a cool, well-ventilated place. Keep

away from sources of ignition - No smoking. Provide sufficient air

exchange and/or exhaust in work rooms.

No data available. Advice on common storage

SECTION 8. Exposure controls/personal protection

Components with workplace control parameters

NATIONAL OCCUPATIONAL EXPOSURE LIMITS

Print Date 08.11.2023 10000003953 6/14



Prop BH

Version 1.01 Revision Date 08.11.2023

Contains no substances with occupational exposure limit values.

Exposure controls

Engineering measures

Provide sufficient air exchange and/or exhaust in work rooms.

Personal protective equipment

Respiratory protection Wear self-contained breathing apparatus and protective suit.

Hand protection Gloves suitable for permanent contact.:

Material: butyl-rubber Break through time: 4 h Material thickness: 0.5 mm Safety glasses with side-shields.

Eye protection Safety glasses with side-shield Skin and body protection Protective suit. Safety shoes.

Hygiene measures Wash hands before breaks and immediately after handling the

product.

SECTION 9. Physical and chemical properties

Information on basic physical and chemical properties

Form Liquid

State of matter Liquid; at 20 °C; 1,013 hPa

ColourColourlessOdourAlcohol-likeOdour ThresholdNo data available.pHNot applicable.

Melting point/range No data available.

Boiling point/boiling range 99 - 113 °C

Flash point 27 °C; closed cup
Evaporation rate No data available.
Flammability (solid, gas) No data available.



Prop BH

Version 1.01 Revision Date 08.11.2023

Auto-ignition temperatureNo data available.DecompositionNo data available.

Temperature

Lower explosion limit1.4 %(V)Upper explosion limit13.7 %(V)

Vapour pressure

Relative vapour density

No data available.

No data available.

No data available.

No data available.

Oensity

0.805 g/cm3; 20 °C

Solubility/qualitative

Completely soluble

Water solubility Completely miscible, Completely soluble

Partition coefficient: n-

octanol/water

No data available.

Viscosity, kinematic 3.46 mm2/s; 20 °C

SECTION 10. Stability and reactivity

Reactivity Stable under recommended storage conditions.

Chemical stability Stable under normal conditions.

Possibility of hazardous

reactions

Heating can release hazardous gases.

Conditions to avoid Heat, flames and sparks.

Materials to avoid Oxidizing agents. Reducing agents. Acids and bases

Hazardous decomposition

products

No decomposition if stored normally.

SECTION 11. Toxicological information

Acute oral toxicity Acute toxicity estimate: 2,500 mg/kg; Calculation method;

Acute inhalation toxicity Acute toxicity estimate: 4 h; vapour; 25 mg/l; Calculation method;

Acute dermal toxicity Acute toxicity estimate: 2,500 mg/kg; Calculation method;

Print Date 08.11.2023 100000003953 8/14



Prop BH

Version 1.01 Revision Date 08.11.2023

Skin irritation Propan-1-ol:

Rabbit: Not irritating; Draize Test (literature value)

Skin irritation Iso-butanol:

Rabbit: Not irritating; (literature value)

Skin irritation n-Butanol:

Rabbit: Irritating; OECD Test Guideline 404 GLP: no; (literature

value)

Eye irritation Propan-1-ol:

Rabbit: Highly irritating 24 - 72 h; (literature value)

Eye irritation Iso-butanol:

Rabbit: Irritating (literature value)

Eye irritation Butan-2-ol:

Rabbit: Irritating OECD Test Guideline 405 1 d; GLP: yes; (literature

value)

Eye irritation n-Butanol:

Rabbit: Irritating GLP: no; (literature value)

Mutagenicity Iso-butanol:

Experiments showed mutagenic effects in cultured bacterial cells.Ames test: Salmonella typhimurium; with and without; Not

mutagenic; (literature value)

Mutagenicity Propan-1-ol:

Ames test: Salmonella typhimurium; Not mutagenic; (literature

value)

Mutagenicity n-Butanol:

Ames test: Salmonella typhimurium; with and without; Not

mutagenic; OECD Test Guideline 471; GLP: no; (literature value)

SECTION 12. Ecological information

Toxicity to fish n-Butanol:

flow-through test; Pimephales promelas; 96 h; LC50; 1,730 mg/l;



Prop BH

Version 1.01 Revision Date 08.11.2023

GLP: no; (literature value)

Toxicity to fish Propan-1-ol:

static test; Pimephales promelas; 96 h; LC50; 4,650 mg/l; GLP: no;

(literature value)

Toxicity to daphnia and other

aquatic invertebrates

n-Butanol:

static test; Daphnia magna; 48 h; EC50; 1,983 mg/IGLP: no;

(literature value)

Toxicity to daphnia and other

aquatic invertebrates

Propan-1-ol:

static test; Daphnia magna (Water flea); 48 h; EC50; 3,644

mg/l(literature value)

Biodegradability n-Butanol:

aerobic; activated sludge of a predominantly domestic sewage; 3

mg/l; 92 %; 20 d; Readily biodegradable.; GLP: no; (literature value)

Biodegradability Iso-butanol:

aerobic; 100 mg/l; > 70 %; 14 d; Readily biodegradable.; OECD

Guideline 301 A (new version); (literature value)

Biodegradability Propan-1-ol:

aerobic; 3 mg/l; 81 %; 20 d; Readily biodegradable.; (literature

value)

Mobility in soil No data available.

Results of PBT and vPvB

assessment

This substance is not considered to be persistent, bioaccumulating

and toxic (PBT). This substance is not considered to be very

persistent and very bioaccumulating (vPvB).

SECTION 13. Disposal considerations

Product Disposal should be in accordance with local, regional and national

legislations.

Packaging Dispose of spent product packaging responsibly and lawfully with

due consideration for health, safety and the environment.

SECTION 14. Transport information



Prop BH

Version 1.01 Revision Date 08.11.2023

DG Pictogram



ADR

UN number: 1987

Class: 3

Packaging group: III; F1;

Proper shipping name: ALCOHOLS, N.O.S.

(n-propanol, butanols)

RID

UN number: 1987

Class: 3

Packaging group: III; F1

Proper shipping name: ALCOHOLS, N.O.S.

(n-propanol, butanols)

ADNR

UN number: 1987

Class: 3

Packaging group: III; F1

Proper shipping name: ALCOHOLS, N.O.S.

(n-propanol, butanols)

IMDG



Prop BH

Version 1.01 Revision Date 08.11.2023

UN number: 1987

Class: 3

EmS: F-E, S-D

Packaging group: III

Proper shipping name: ALCOHOLS, N.O.S.

(n-propanol, butanols)

Marine pollutant Not a Marine Pollutant

ICAO/IATA

UN number: 1987

Class: 3

Packaging group: III

Proper shipping name: ALCOHOLS,N.O.S.

(n-propanol, butanols)

Transport in bulk according Noxious liquid. NF, (8) n.o.s (Prop BH, contains-n-Propyl alcohol)

to Annex II of MARPOL

73/78 and the IBC Code Ship Type: 3

POLLUTION CATEGORY: Y

SECTION 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

USA TSCA Inventory All chemical constituents are listed in: USA TSCA Inventory (See

chapter 3)

Canadian Domestic Substances List (DSL)

All chemical constituents are listed in: Canadian Domestic Substances

List (DSL) (See chapter 3)

Print Date 08.11.2023 100000003953 12/14



Prop BH

Version 1.01 Revision Date 08.11.2023

Australian Inv. of Chem. Substances (AICS) All chemical constituents are listed in: Australian Inv. of Chem. Substances (AICS) (See chapter 3) All chemical constituents are listed in: New Zealand Inventory of **New Zealand Inventory of Chemicals (NZIoC)** Chemicals (NZIoC) (See chapter 3) Jap. Inv. of Exist. & New Chemicals (ENCS) All chemical constituents are listed in: Jap. Inv. of Exist. & New Chemicals (ENCS) (See chapter 3) Japan. Industrial Safety & Health Law (ISHL) All chemical constituents are listed in: Japan. Industrial Safety & Health Law (ISHL) (See chapter 3) **Korea. Existing Chemicals Inventory (KECI)** All chemical constituents are listed in: Korea. Existing Chemicals Inventory (KECI) (See chapter 3) Philippines Inventory of Chemicals and All chemical constituents are listed in: Philippines Inventory of **Chemical Substances (PICCS)** Chemicals and Chemical Substances (PICCS) (See chapter 3) China Inv. Existing Chemical Substances All chemical constituents are listed in: China Inv. Existing Chemical Substances (IECSC) (See chapter 3) (IECSC)

SECTION 16. Other information

Full text of H-Statements

H225

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H303	May be harmful if swallowed.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
	~

Highly flammable liquid and vapour.

H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

All reasonable efforts were exercised to compile this SDS in accordance with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS). The SDS only provides information regarding the health, safety and environmental hazards at the date of issue, to facilitate the safe receipt, use and handling of this product in the workplace and does not replace any product information or product specifications. Since Sasol and its subsidiaries cannot anticipate or control all conditions under which this product may be handled, used and received in the workplace, it remains the obligation of each user, receiver or handler to, prior to usage, review this SDS in the context within which this product will be received,



Prop BH

Version 1.01 Revision Date 08.11.2023

handled or used in the workplace. The user, handler or receiver must ensure that the necessary mitigating measures are in place with respect to health and safety. This does not substitute the need or requirement for any relevant risk assessments to be conducted. It further remains the responsibility of the receiver, handler or user to communicate such information to all relevant parties that may be involved in the receipt, use or handling of this product.

Although all reasonable efforts were exercised in the compilation of this SDS, Sasol does not expressly warrant the accuracy of, or assume any liability for incomplete information contained herein or any advice given. When this product is sold, risk passes to the purchaser in accordance with the specific terms and conditions of sale.