



Safety Data Sheet

Hydraulic Fluid Metal Free 46

Version 1.01

Revision Date 26.06.2023

SECTION 1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name

Hydraulic Fluid Metal Free 46

Synonyms

Hydraulic Fluid

Relevant identified uses of the substance or mixture and uses advised against

Use

Lubricant or lubricant additive

Manufacturer or supplier's details

Company

Sasol Oil Pty (Ltd)

Address

Sasol Place, 50 Katherine Street
Sandton
2090
South Africa
+27860335444

Telephone

E-mail address

sasolchem.info.sa@sasol.com

Emergency telephone number

+44 (0)1235 239 670 (Europe, Israel, Africa, Americas)

+44(0)1235 239 671 (Middle East, Arabic African countries)

+65 3158 1074 (Asia Pacific)

+86 10 5100 3039 (China)

+27 (0)17 610 4444 (South Africa)

+61 (2) 8014 4558 (Australia)

Safety Data Sheet

Hydraulic Fluid Metal Free 46

Version 1.01

Revision Date 26.06.2023

SECTION 2. Hazards identification

Classification of the substance or mixture

Classification **REGULATION (EC) No 1272/2008**

Skin sensitisation

Category 1

Label elements

Pictogram



Signal word

Warning

Hazard statements

H317: May cause an allergic skin reaction.

Precautionary statements

Prevention

P261: Avoid breathing mist or vapours.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves.

Response

P302 + P352: IF ON SKIN: Wash with plenty of soap and water.

P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.

Safety Data Sheet

Hydraulic Fluid Metal Free 46

Version 1.01

Revision Date 26.06.2023

P362 + P364: Take off contaminated clothing and wash it before reuse.

Storage No special storage conditions required.

Disposal P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards No data available

SECTION 3. Composition/information on ingredients

Mixture

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified

Contents: 99.00 %W/W

CAS-No. 64742-54-7

Index-No. 649-467-00-8

EC-No. 265-157-1

Hazard statements *H304*

Mineral Oil

Contents: 0.24 %W/W

CAS-No.

Index-No.

EC-No.

Hazard statements *H304*

Benzenamine, N-phenyl-, styrenated

Contents: ≥ 0.15 - ≤ 0.30 %W/W

CAS-No. 68442-68-2

Index-No.

EC-No. 270-485-3

Hazard statements *H413 H412*

Safety Data Sheet

Hydraulic Fluid Metal Free 46

Version 1.01

Revision Date 26.06.2023

2,6-di-tert-butylphenol

Contents: ≥ 0.11 - ≤ 0.14 %W/W

CAS-No. 128-39-2

Index-No.

EC-No. 204-884-0

Hazard statements *H315 H400 H410*

3-(O,Odiisobutyldithio phosphoryl)-2-methylpropanoic acid

Contents: ≤ 0.06 %W/W

CAS-No. 268567-32-4

Index-No.

EC-No.

Hazard statements *H318 H317 H412*

1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-ar-methyl

Contents: ≤ 0.06 %W/W

CAS-No. 94270-86-7

Index-No.

EC-No.

Hazard statements *H315 H317 H400 H411*

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4. First aid measures

Description of necessary first-aid measures

Inhalation

Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If breathing is difficult, give oxygen. Get medical attention/advice if you feel unwell.

Skin contact

Wash off immediately with soap and plenty of water. Wash contaminated clothing before reuse. Get medical attention if

Safety Data Sheet

Hydraulic Fluid Metal Free 46

Version 1.01

Revision Date 26.06.2023

	irritation develops and persists.
Eye contact	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek immediate medical attention/advice.
Ingestion	Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Seek immediate medical attention/advice.
Most important symptoms/effects, acute and delayed	

Refer to SECTION 11

SECTION 5. Firefighting measures

Suitable extinguishing media	Water spray, Foam, CO ₂ , Dry powder.
Special hazards arising from the substance or mixture	Under conditions of continuous exposure to heat, may burn. Under extreme conditions (e.g. confinement) could lead to detonation. Nitrogen oxides (NO _x) and carbon oxides are produced during combustion.
Special protective equipment for firefighters	Wear self-contained breathing apparatus and protective suit.

SECTION 6. Accidental release measures

Safety Data Sheet

Hydraulic Fluid Metal Free 46

Version 1.01

Revision Date 26.06.2023

Personal precautions	Use personal protective equipment. Handle in accordance with good industrial hygiene and safety practice.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Try to prevent the material from entering drains or water courses.
Methods for cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Disposal and clean up may only be done by authorised personnel.
Reference to other sections	Refer toSection8and13

SECTION 7. Handling and storage

Safe handling advice	Wear personal protective equipment. Do not breathe vapours or spray mist. Avoid contact with skin and eyes. Ensure adequate ventilation. Keep away from flames and sparks.
Advice on protection against fire and explosion	No data available
Requirements for storage areas and containers	Keep away from heat.Do not store near combustible materials.
Advice on common storage	No data available

SECTION 8. Exposure controls/personal protection

Components with workplace control parameters

NATIONAL OCCUPATIONAL EXPOSURE LIMITS

Contains no substances with occupational exposure limit values.

Safety Data Sheet

Hydraulic Fluid Metal Free 46

Version 1.01

Revision Date 26.06.2023

Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection Gloves suitable for permanent contact:
Material: butyl-rubber
Break through time: 4 h
Material thickness: 0.5 mm

Eye protection Safety goggles

Skin and body protection lightweight protective clothing

Hygiene measures Wash hands before breaks and immediately after handling the product.

SECTION 9. Physical and chemical properties

Information on basic physical and chemical properties

Form	Liquid
State of matter	Liquid; at 20 ° C; 1,013 hPa
Colour	amber
Odour	mild

Safety Data Sheet

Hydraulic Fluid Metal Free 46

Version 1.01

Revision Date 26.06.2023

Odour Threshold	No data available
pH	No data available
Pour point	-18 ° C; ASTM D97
Flash point	200 ° C; ASTM D92
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Auto-ignition temperature	No data available
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapour pressure	No data available
Relative vapour density	No data available
Density	0.871 g/cm ³ ; ASTM D4052
Water solubility	immiscible, Insoluble
Partition coefficient: n-octanol/water	No data available
Viscosity, kinematic	46 mm ² /s; ASTM D 445

SECTION 10. Stability and reactivity

Reactivity	Stable under normal conditions.
Chemical stability	No data available
Possibility of hazardous	Strong acids and oxidizing agents

Safety Data Sheet

Hydraulic Fluid Metal Free 46

Version 1.01

Revision Date 26.06.2023

reactions

Conditions to avoid No data available

Materials to avoid Combustible material

Hazardous decomposition products Stable under normal conditions.

SECTION 11. Toxicological information

Acute oral toxicity	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified: LD50 Rat: 5,000 mg/kg;
Acute inhalation toxicity	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified: LC50 Rat: 4 h; 2.18 - 5.53 mg/l;
Acute dermal toxicity	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified: LD50 Rabbit: 2,000 - 5,000 mg/kg;
Repeated dose toxicity	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified: Oral Rat; Lowest observed adverse effect level 125 mg/kg
Repeated dose toxicity	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified: Dermal Rat; NOAEL Early embryonic development 30 - 2,000 mg/kg
Repeated dose toxicity	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified:

Safety Data Sheet

Hydraulic Fluid Metal Free 46

Version 1.01

Revision Date 26.06.2023

	Dermal Mouse; NOAEL Early embryonic development 150 mg/kg Lowest observed adverse effect level 100 mg/kg
Repeated dose toxicity	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified: Dermal Rabbit; NOAEL Early embryonic development 1,000 mg/kg
Carcinogenicity	Mineral oils are severely solvent refined or hydrotreated.

SECTION 12. Ecological information

Toxicity to fish	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified: 4 d; LL50; 100 mg/l;
Toxicity to daphnia and other aquatic invertebrates	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified: No data available
Toxicity to algae	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified: No data available
Toxicity to bacteria	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified: No data available

SECTION 13. Disposal considerations

Product	Dispose of in accordance with local regulations.
----------------	--



Safety Data Sheet

Hydraulic Fluid Metal Free 46

Version 1.01

Revision Date 26.06.2023

SECTION 14. Transport information

Further Information

Not classified as dangerous in the meaning of transport regulations.

SECTION 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Canadian Domestic Substances List (DSL)	Components Not listed Mineral Oil
Australian Inv. of Chem. Substances (AICS)	Components Not listed Mineral Oil
New Zealand Inventory of Chemicals (NZIoC)	Components Not listed Mineral Oil
Jap. Inv. of Exist. & New Chemicals (ENCS)	Components Not listed Distillates (petroleum), hydrotreated heavy paraffinic Mineral Oil 2,6-di-tert-butylphenol
Japan. Industrial Safety & Health Law (ISHL)	Components Not listed Distillates (petroleum), hydrotreated heavy paraffinic Mineral Oil 2,6-di-tert-butylphenol
Korea. Existing Chemicals Inventory (KECI)	Components Not listed Mineral Oil
Philippines Inventory of Chemicals and	Components Not listed



Safety Data Sheet

Hydraulic Fluid Metal Free 46

Version 1.01

Revision Date 26.06.2023

Chemical Substances (PICCS)	Mineral Oil
China Inv. Existing Chemical Substances (IECSC)	Components Not listed Mineral Oil
Taiwan. Chemical Substances Inventory (TCSI)	Components Not listed Mineral Oil
USA TSCA Inventory	Components Not listed Mineral Oil

SECTION 16. Other information

Full text of H-Statements

- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

All reasonable efforts were exercised to compile this SDS in accordance with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS). The SDS only provides information regarding the health, safety and environmental hazards at the date of issue, to facilitate the safe receipt, use and handling of this product in the workplace and does not replace any product information or product specifications. Since Sasol and its subsidiaries cannot anticipate or control all conditions under which this product may be handled, used and received in the workplace, it remains the obligation of each user, receiver or handler to, prior to usage, review this



Safety Data Sheet

Hydraulic Fluid Metal Free 46

Version 1.01

Revision Date 26.06.2023

SDS in the context within which this product will be received, handled or used in the workplace. The user, handler or receiver must ensure that the necessary mitigating measures are in place with respect to health and safety. This does not substitute the need or requirement for any relevant risk assessments to be conducted. It further remains the responsibility of the receiver, handler or user to communicate such information to all relevant parties that may be involved in the receipt, use or handling of this product.

Although all reasonable efforts were exercised in the compilation of this SDS, Sasol does not expressly warrant the accuracy of, or assume any liability for incomplete information contained herein or any advice given. When this product is sold, risk passes to the purchaser in accordance with the specific terms and conditions of sale.