

Acetone

Version 1.02 Revision Date 30.03.2021

SECTION 1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name Acetone

Synonyms 2-Propanone, methyl ketone, Ketone propane, beta-

Ketopropane

Product code 2110

CAS-No. 67-64-1

EINECS-No. 200-662-2

Relevant identified uses of the substance or mixture and uses advised against

Use Industrial use. Solvent

Manufacturer or supplier's details

Company Sasol Chemicals, a division of Sasol South Africa Ltd

Address Sasol Place, 50 Katherine Street

Sandton 2090

South Africa

Telephone +27103445000

E-mail address sasolchem.info.sa@sasol.com

Supplier's details Sasol Chemicals Pacific Ltd

2 Shenton way #06-01

SGX Centre 1

068804 Singapore

Telephone +65 6533 8856

Print Date 30.03.2021 100000003894 1/15



Acetone

Version 1.02 Revision Date 30.03.2021

E-mail address info.sg@sasol.com

Emergency Phone Number

Emergency telephone +44 (0)1235 239 670 (Europe, Israel, Africa, Americas)

+44(0)1235 239 671 (Middle East, Arabic African countries)

+65 3158 1074 (Asia Pacific)

+86 400 120 6011 (China)

+27 (0)17 610 4444 (South Africa)

0800 112 890 RSA-Local only

+61 (2) 8014 4558 (Australia)

SECTION 2. Hazards identification

Classification of the substance or mixture

GHS Classification

Globally Harmonized System of Classification and Labeling of

Chemicals (GHS)

Classification Flammable liquids Category 2

Eye damage/irritation Category 2

Specific target organ toxicity - single exposure Category 3

GHS label elements

Print Date 30.03.2021 100000003894 2/15



Acetone

Version 1.02 Revision Date 30.03.2021

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statements : Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water/

shower.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:



Acetone

Version 1.02

Revision Date 30.03.2021

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



Acetone

Version 1.02 Revision Date 30.03.2021

SECTION 3. Composition/information on ingredients

Substance

Acetone

Contents: >= 90.00 - <= 100.00 %W/W

CAS-No. 67-64-1 **Index-No.** 606-001-00-8 **EC-No.** 200-662-2

Hazard Statements H225 H319 H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4. First aid measures

Description of necessary first-aid measures

Inhalation Move to fresh air in case of accidental inhalation of vapors. If

breathing is irregular or stopped, administer artificial

respiration. Call a physician immediately.

Skin contact Wash off immediately with soap and plenty of water while

removing all contaminated clothes and shoes. Wash

contaminated clothing before re-use. If skin irritation persists,

call a physician.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes

and consult a physician.

Ingestion If swallowed, seek medical advice immediately and show this

container or label. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious

person.



Acetone

Version 1.02 Revision Date 30.03.2021

Most important symptoms/effects, acute and delayed

Refer to SECTION 11

SECTION 5. Firefighting measures

Suitable extinguishing Water spray Alcohol-resistant foam Dry chemical. Carbon

media dioxide.

Unsuitable extinguishing

media

No information available.

Special hazards arising

from the substance or

mixture

Flash back possible over considerable distance. Vapors may

form explosive mixtures with air.

Special protective

equipment for firefighters

Wear self-contained breathing apparatus and protective suit.

SECTION 6. Accidental release measures

Personal precautions Keep people away from and upwind of spill/leak. Remove all

sources of ignition. Do not breathe vapors or spray mist.

Ensure adequate ventilation.

Environmental precautions Should not be released into the environment. Prevent further

leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Do not flush into surface

water or sanitary sewer system.

Print Date 30.03.2021 100000003894 6/15



Acetone

Version 1.02 Revision Date 30.03.2021

Methods for cleaning up Soak up with inert absorbent material and dispose of as

hazardous waste.

Reference to other sections Refer to Section 8 and 13

SECTION 7. Handling and storage

Safe handling advice Provide sufficient air exchange and/or exhaust in work rooms.

Wear personal protective equipment. Take precautionary measures against static discharges. Ensure all equipment is electrically grounded before beginning transfer operations.

Advice on protection

Keep away from open flames, hot surfaces and sources of

against fire and explosion

ignition.Use explosion-proof equipment.

Temperature class T1

Requirements for storage

areas and containers

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat. Keep away from direct sunlight.

Advice on common storage Keep containers tightly closed in a cool, well-ventilated place.

SECTION 8. Exposure controls/personal protection

Ingredients with workplace control parameters

NATIONAL OCCUPATIONAL EXPOSURE LIMITS

Components	Туре	Control	Update	Basis
		parameters		



Acetone

Version 1.02 Revision Date 30.03.2021

ASETON	TWA	1,187.12	11 2011	Indonesia OELs Hazard
ASETON	TWA	mg/m3	11 2011	Data
	STEL	500 ppm	11 2011	Indonesia OELs Hazard
	STEL	1,780 mg/m3	11 2011	Data
		750 ppm		Indonesia OELs Hazard
				Data
				Indonesia OELs Hazard
				Data

Exposure controls

Engineering measures

Provide sufficient air exchange and/or exhaust in work rooms.

Personal protective equipment

Respiratory protection In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection Gloves suitable for permanent contact:

Material: butyl-rubber Break through time: 4 h Material thickness: 0.5 mm

Eye protection Safety glasses with side-shields

Skin and body protection Protective suit Safety shoes

Hygiene measures Wash hands before breaks and immediately after handling the

product. Take off all contaminated clothing immediately.

SECTION 9. Physical and chemical properties



Acetone

Version 1.02 Revision Date 30.03.2021

Information on basic physical and chemical properties

Form Liquid

State of matter Liquid; at 20 ° C; 1,013 hPa

Color Colorless

Odor characteristic

Odor Threshold No data available

Melting point/range -95 ° C

Boiling point/boiling range 56 ° C

Flash point -20 ° C; closed cup

Evaporation rate No data available

Flammability (solid, gas) No data available

Autoignition temperature 465 ° C

Decomposition

Temperature

Lower explosion limit 2.6 %(V)

Upper explosion limit 12.8 %(V)

Vapor pressure 307 hPa; 25 ° C

Relative vapor density 2

Density 0.79 g/cm3

Water solubility soluble

Viscosity, dynamic 0.32 mPa.s

Viscosity, kinematic 0.4 mm2/s



Acetone

Version 1.02 Revision Date 30.03.2021

SECTION 10. Stability and reactivity

Reactivity Stable under recommended storage conditions.

Chemical stability No data available

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Extremes of temperature and direct sunlight. Heat, flames and

sparks.

Materials to avoid Strong oxidizing agents Incompatible with acids. Halogenated

compounds

Hazardous decomposition

products

Carbon oxides

SECTION 11. Toxicological information

Acute oral toxicity Acetone:

LD50 Rat: > 2,000 mg/kg; (literature value)

Acute inhalation toxicity Acetone:

LC50 Rat: 4 h; vapor; > 20 mg/l; GLP: no; (literature value)

Acute dermal toxicity Acetone:

LD50 Rabbit: > 2,000 mg/kg; (literature value)

Skin irritation Acetone:

Rabbit: irritating; GLP: no; (literature value)

Eye irritation Acetone:

Print Date 30.03.2021 100000003894 10/15



Acetone

Version 1.02 Revision Date 30.03.2021

Rabbit: irritating GLP: no; (literature value)

Mutagenicity Acetone:

Ames test: Salmonella typhimurium; Not mutagenic; GLP: no;

(literature value)

SECTION 12. Ecological information

Toxicity to daphnia and other Acetone:

aquatic invertebrates static test; Daphnia magna (Water flea); 48 h; > 100

mg/l(literature value)

Biodegradability Acetone:

Readily biodegradable.; (literature value)

SECTION 13. Disposal considerations

Product In accordance with local and national regulations. Do not

contaminate ponds, waterways or ditches with chemical or used container. The product should not be allowed to enter

drains, water courses or the soil.

Packaging Dispose of spent product packaging responsibly and lawfully

with due consideration for health, safety and the

environment.

SECTION 14. Transport information

Print Date 30.03.2021 100000003894 11/15



Acetone

Version 1.02 Revision Date 30.03.2021

DG Pictogram



ADR

UN number: 1090

Class: 3

Packaging group: II; F1;

Proper shipping name: ACETONE

RID

UN number: 1090

Class: 3

Packaging group: II; F1

Proper shipping name: ACETONE

ADNR

UN number: 1090

Class: 3

Packaging group: II; F1

Proper shipping name: ACETONE

IMDG



Acetone

Version 1.02 Revision Date 30.03.2021

UN number: 1090

Class: 3

EmS: F-E, S-D

Packaging group:

Proper shipping name: ACETONE

Marine pollutant Not a Marine Pollutant

ICAO/IATA

UN number: 1090

Class: 3

Packaging group:

Proper shipping name: ACETONE

Transport in bulk according Acetone

to Annex II of MARPOL 73/78 and the IBC Code

Pollution Category: Z

SECTION 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Canada. DSL - Domestic Substances List, All chemical constituents are listed in: Canada. DSL - Domestic

part of CEPA Substances List, part of CEPA (See chapter 3)

Print Date 30.03.2021 100000003894 13/15



Acetone

Version 1.02 Revision Date 30.03.2021

Australia. AICS - Australian Inventory of Chemical Substances	All chemical constituents are listed in: Australia. AICS - Australian Inventory of Chemical Substances (See chapter 3)
New Zealand Inventory of Chemical Substances	All chemical constituents are listed in: New Zealand Inventory of Chemical Substances (See chapter 3)
Japan. ENCS - Existing and New Chemical Substances Inventory	All chemical constituents are listed in: Japan. ENCS - Existing and New Chemical Substances Inventory (See chapter 3)
Japan. Industrial Safety and Health Law - Inventory	All chemical constituents are listed in: Japan. Industrial Safety and Health Law - Inventory (See chapter 3)
Korea. KECI - Korean Existing Chemicals Inventory	All chemical constituents are listed in: Korea. KECI - Korean Existing Chemicals Inventory (See chapter 3)
Philippines. PICCS - Philippines Inventory of Chemicals and Chemical Substances	All chemical constituents are listed in: Philippines. PICCS - Philippines Inventory of Chemicals and Chemical Substances (See chapter 3)
China. IECSC - Inventory of Existing Chemical Substances in China	All chemical constituents are listed in: China. IECSC - Inventory of Existing Chemical Substances in China (See chapter 3)
Taiwan. Chemical Substances Inventory (TCSI)	All chemical constituents are listed in: Taiwan. Chemical Substances Inventory (TCSI) (See chapter 3)
USA TSCA Inventory	All chemical constituents are listed in: USA TSCA Inventory (See chapter 3)

SECTION 16. Other information

Full text of H-Statements

Print Date 30.03.2021 100000003894 14/15



Acetone

Version 1.02

Revision Date 30.03.2021

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

All reasonable efforts were exercised to compile this SDS in accordance with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS). The SDS only provides information regarding the health, safety and environmental hazards at the date of issue, to facilitate the safe receipt, use and handling of this product in the workplace and does not replace any product information or product specifications. Since Sasol and its subsidiaries cannot anticipate or control all conditions under which this product may be handled, used and received in the workplace, it remains the obligation of each user, receiver or handler to, prior to usage, review this SDS in the context within which this product will be received, handled or used in the workplace. The user, handler or receiver must ensure that the necessary mitigating measures are in place with respect to health and safety. This does not substitute the need or requirement for any relevant risk assessments to be conducted. It further remains the responsibility of the receiver, handler or user to communicate such information to all relevant parties that may be involved in the receipt, use or handling of this product.

Although all reasonable efforts were exercised in the compilation of this SDS, Sasol does not expressly warrant the accuracy of, or assume any liability for incomplete information contained herein or any advice given. When this product is sold, risk passes to the purchaser in accordance with the specific terms and conditions of sale.