

Penetration grade bitumen (35/50)

Version 1.00 Revision Date 12.06.2023

SECTION 1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name Penetration grade bitumen (35/50)

Synonyms Penetration grade bitumen, Asphalt, Petroleum residue, Road

binder

Relevant identified uses of the substance or mixture and uses advised against

Use Research and development. Raw material for adhesives and

binders. Raw material for stabilizers surface-active substance

Emulsifying agent.

Manufacturer or supplier's details

Company Sasol Oil Pty (Ltd)

Address Sasol Place, 50 Katherine Street

Sandton 2090 South Africa

Telephone +27860335444

E-mail address sasolchem.info.sa@sasol.com

Emergency telephone number South Africa: 0800 11 28 90; International: +27 17 610 4444

SECTION 2. Hazards identification

Classification of the substance or mixture

REGULATION (EC) No 1272/2008

The substance or mixture is not classified Classification

according to the CLP regulation.

Label elements

Hazard statements NA This substance or mixture is not classified as

Print Date 12.06.2023 **100000011165** 1/9



Penetration grade bitumen (35/50)

Version 1.00 Revision Date 12.06.2023

hazardous according to GHS.

Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3. Composition/information on ingredients

Substance

asphalt

Contents: >= 90.00 - <= 100.00 %W/W

CAS-No. 8052-42-4 Index-No. EC-No. 232-490-9

Print Date 12.06.2023 **100000011165** 2/9



Penetration grade bitumen (35/50)

Version 1.00 Revision Date 12.06.2023

SECTION 4. First aid measures

Description of necessary first-aid measures

Inhalation Move to fresh air in case of accidental inhalation of vapours.

Skin contact Hot product can cause thermal burns. Wash off immediately

Hot product can cause thermal burns. Wash off immediately with plenty of water. If symptoms persist, call a physician.

Eye contact If hot product is splashed into eyes flush with water and get

immediate attention.

Ingestion Not expected to be a problem. However, if discomfort occurs

seek medical attention.

Most important symptoms/effects, acute and delayed

Refer to SECTION 11

SECTION 5. Firefighting measures

Suitable extinguishing Foam. Carbon dioxide. Dry chemical.

media

Unsuitable extinguishing Water.

media

Special hazards arising Burning produces irritant fumes.

from the substance or

mixture

Special protective In the event of fire, wear self-contained breathing apparatus.

equipment for firefighters Use personal protective equipment.

SECTION 6. Accidental release measures

Environmental precautions Prevent product from entering drains.

Methods for cleaning up Sweep up and shovel. Shovel into suitable container for

disposal. Bitumens are immiscible with water but may be adsorped in the sediment. Surface material may be skimmed

off for later disposal.



Penetration grade bitumen (35/50)

Version 1.00 Revision Date 12.06.2023

Reference to other sections Refer to section 8 and 13

SECTION 7. Handling and storage

Safe handling advice Bitumen is commonly handled as a liquid at temperatures

above 100° C Wear personal protective equipment. Avoid

exposure of heated material atmosphere or oxygen

Advice on protection

against fire and explosion

Keep away from heat and sources of ignition.

Requirements for storage

areas and containers

Avoid local overheating when raising to pumping temperature. Where hot bitumen is handled in confined spaces, half-face respirators and effective local artificial ventilation should be

provided if possible.

Advice on common storage Stored at elevated temperatures: 150° C - 170° C in bulk

tanks

SECTION 8. Exposure controls/personal protection

Components with workplace control parameters

NATIONAL OCCUPATIONAL EXPOSURE LIMITS

Components	Туре	Control	Update	Basis
		parameters		
ASPHALT, PETROLEUM	TWA	5 mg/m3	1995	South Africa RELs
FUMES	STEL	10 mg/m3	1995	South Africa RELs
ASPHALT, PETROLEUM				
FUMES				

Exposure controls

Engineering measures

Provide sufficient air exchange and/or exhaust in work rooms.



Penetration grade bitumen (35/50)

Version 1.00 Revision Date 12.06.2023

Personal protective equipment

Respiratory protection In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection Heat insulating gloves, Chemical-resistant gloves with close-

fitting cuffs

Eye protection Safety goggles and a full-face shield to be worn.

Hygiene measures Wash hands before breaks and immediately after handling the

product.

SECTION 9. Physical and chemical properties

Information on basic physical and chemical properties

Form Solid

State of matter Solid; at 20 ° C; 1,013 hPa

ColourDark brown to blackOdourStrong CharacteristicOdour ThresholdNo data available.pHNo data available.

Softening point $49 - 59 \degree C$ Boiling point/boiling range $> 530 \degree C$ Flash point $> 230 \degree C$

Evaporation rate No data available. Flammability (solid, gas) No data available. Auto-ignition temperature No data available. No data available. Lower explosion limit Upper explosion limit No data available. No data available. Vapour pressure Relative vapour density No data available. No data available. **Density** Water solubility Insoluble, Immiscible Partition coefficient: n-No data available.

octanol/water

Viscosity, dynamic No data available.



Penetration grade bitumen (35/50)

Version 1.00 Revision Date 12.06.2023

SECTION 10. Stability and reactivity

Reactivity Stable under recommended storage conditions.

Chemical stability No data available.

Possibility of hazardous

reactions

No data available.

Conditions to avoid Direct sources of heat. Overheating may result in thermal

cracking that produces toxic and flammable vapours.

Materials to avoid Oxidizing agents. Strong acids Alkali metals. Halogens.

Hazardous decomposition

Carbon oxides.

products

SECTION 11. Toxicological information

Acute oral toxicity LD50 Rat: 5,000 mg/kg;
Acute dermal toxicity LD50 Rabbit: 2,000 mg/kg;

Repeated dose toxicity Dermal Rabbit; NOAEL Early embryonic development 200 -

2,000 mg/kg Lowest observed adverse effect level 200 mg/kg

SECTION 12. Ecological information

Toxicity to fish No data available.

Toxicity to bacteria No data available.

Other adverse effects This product has no known ecotoxicological effects.

SECTION 13. Disposal considerations

Product Can be landfilled or incinerated, when in compliance with

local regulations.

SECTION 14. Transport information

Print Date 12.06.2023 100000011165 6/9



Penetration grade bitumen (35/50)

Version 1.00 Revision Date 12.06.2023

DG Pictogram



ADR

UN number: 3257
Class: 9
Packaging group: III; M9;

Proper shipping name: ELEVATED TEMPERATURE LIQUID, N.O.S.

RID

UN number: 3257 **Class:** 9

Packaging group: III; M9

Proper shipping name: ELEVATED TEMPERATURE LIQUID, N.O.S.

ADNR

UN number: 3257
Class: 9
Packaging group: III; M9

Proper shipping name: ELEVATED TEMPERATURE LIQUID, N.O.S.

IMDG

UN number: 3257 **Class:** 9

EmS: F-A, S-P

Packaging group:

Proper shipping name: ELEVATED TEMPERATURE LIQUID, N.O.S.

ICAO/IATA

UN number : 3257 **Class:** 9

Proper shipping name: ELEVATED TEMPERATURE LIQUID, N.O.S.

SECTION 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Print Date 12.06.2023 100000011165 7/9



Penetration grade bitumen (35/50)

Version 1.00 Revision Date 12.06.2023

Canada. DSL - Domestic Substances List, part of CEPA	All chemical constituents are listed in: Canada. DSL - Domestic Substances List, part of CEPA (See chapter 3)
Australia. AICS - Australian Inventory of Chemical Substances	All chemical constituents are listed in: Australia. AICS - Australian Inventory of Chemical Substances (See chapter 3)
New Zealand Inventory of Chemical Substances	All chemical constituents are listed in: New Zealand Inventory of Chemical Substances (See chapter 3)
Japan. ENCS - Existing and New Chemical Substances Inventory	All chemical constituents are listed in: Japan. ENCS - Existing and New Chemical Substances Inventory (See chapter 3)
Japan. Industrial Safety and Health Law - Inventory	All chemical constituents are listed in: Japan. Industrial Safety and Health Law - Inventory (See chapter 3)
Korea. KECI - Korean Existing Chemicals Inventory	All chemical constituents are listed in: Korea. KECI - Korean Existing Chemicals Inventory (See chapter 3)
Philippines. PICCS - Philippines Inventory of Chemicals and Chemical Substances	All chemical constituents are listed in: Philippines. PICCS - Philippines Inventory of Chemicals and Chemical Substances (See chapter 3)
China. IECSC - Inventory of Existing Chemical Substances in China	All chemical constituents are listed in: China. IECSC - Inventory of Existing Chemical Substances in China (See chapter 3)
Taiwan. Chemical Substances Inventory (TCSI)	All chemical constituents are listed in: Taiwan. Chemical Substances Inventory (TCSI) (See chapter 3)
USA TSCA Inventory	All chemical constituents are listed in: USA TSCA Inventory (See chapter 3)

SECTION 16. Other information

Full text of H-Statements.

This substance contains no components with H-statement.

All reasonable efforts were exercised to compile this SDS in accordance with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS). The SDS only provides information regarding the health, safety and environmental hazards at the date of issue, to facilitate the safe receipt, use and handling of this product in



Penetration grade bitumen (35/50)

Version 1.00 Revision Date 12.06.2023

the workplace and does not replace any product information or product specifications. Since Sasol and its subsidiaries cannot anticipate or control all conditions under which this product may be handled, used and received in the workplace, it remains the obligation of each user, receiver or handler to, prior to usage, review this SDS in the context within which this product will be received, handled or used in the workplace. The user, handler or receiver must ensure that the necessary mitigating measures are in place with respect to health and safety. This does not substitute the need or requirement for any relevant risk assessments to be conducted. It further remains the responsibility of the receiver, handler or user to communicate such information to all relevant parties that may be involved in the receipt, use or handling of this product.

Although all reasonable efforts were exercised in the compilation of this SDS, Sasol does not expressly warrant the accuracy of, or assume any liability for incomplete information contained herein or any advice given. When this product is sold, risk passes to the purchaser in accordance with the specific terms and conditions of sale.

Print Date 12.06.2023 **100000011165** 9/9