

Hydraulic Fluid HVI 68

Version 1.01 Revision Date 07.09.2023

SECTION 1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Telephone

Hydraulic Fluid HVI 68 Trade name

Hydraulic Fluid **Synonyms**

Relevant identified uses of the substance or mixture and uses advised against

Use Lubricant or lubricant additive

Manufacturer or supplier's details

Sasol Oil Pty (Ltd) Company

Sasol Place, 50 Katherine Street Address

Sandton 2090

South Africa +27860335444

E-mail address sasolchem.info.sa@sasol.com

Emergency telephone number +44 (0)1235 239 670 (Europe, Israel, Africa, Americas)

+44(0)1235 239 671 (Middle East, Arabic African countries)

+65 3158 1074 (Asia Pacific)

+86 10 5100 3039 (China)

+27 (0)17 610 4444 (South Africa)

+61 (2) 8014 4558 (Australia)



Hydraulic Fluid HVI 68

Version 1.01 Revision Date 07.09.2023

SECTION 2. Hazards identification

Classification of the substance or mixture

REGULATION (EC) No 1272/2008

Classification

The mixture is not classified as hazardous according

to GHS.

Label elements

Pictogram Not applicable

Signal word Not applicable

Hazard statements The mixture is not classified as hazardous according to GHS.

Precautionary statements

Prevention The mixture is not classified as hazardous according to GHS.

Response The mixture is not classified as hazardous according to GHS.

Storage No special storage conditions required.

Disposal Dispose of contents/container in accordance with local regulation.

Other hazards No data available

SECTION 3. Composition/information on ingredients

Print Date 07.09.2023 100000006488 2/13



Hydraulic Fluid HVI 68

Version 1.01 Revision Date 07.09.2023

Mixture

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified

Contents: <= 99.04 %W/W

CAS-No. 64742-54-7 **Index-No**. 649-467-00-8 **EC-No**. 265-157-1

Hazard statements H304

Acrylic copolymer

Contents: >= 3.30 - <= 5.50 %W/W

CAS-No. Index-No. EC-No.

Mineral Oil

Contents: >= 0.91 - <= 2.37 %W/W

CAS-No. Index-No. EC-No.

Hazard statements H304

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate

Contents: <= 0.06 %W/W

CAS-No. 80-62-6 **Index-No.** 607-035-00-6 **EC-No.** 201-297-1

Hazard statements H225 H315 H317 H335 H402

Zinc dialkyl dithiophosphate

Contents: >= 0.26 - <= 0.51 %W/W

CAS-No. Index-No. EC-No.

Hazard statements H315 H318 H319 H411



Hydraulic Fluid HVI 68

Version 1.01 Revision Date 07.09.2023

Alkyl Phenol (isomer)

Contents: >= 0.09 - <= 0.17 %W/W

CAS-No. Index-No. EC-No.

Hazard statements H315 H400 H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4. First aid measures

Description of necessary first-aid measures

Inhalation Move to fresh air in case of accidental inhalation of vapours. If

breathing is irregular or stopped, administer artificial

respiration. If breathing is difficult, give oxygen. Get medical

attention/advice if you feel unwell.

Skin contact Wash off immediately with soap and plenty of water. Wash

contaminated clothing before reuse. Get medical attention if

irritation develops and persists.

Eye contact Remove contact lenses. Rinse immediately with plenty of

water, also under the eyelids, for at least 15 minutes. Seek

immediate medical attention/advice.

Ingestion Do not induce vomiting without medical advice. Never give

anything by mouth to an unconscious person. Seek immediate

medical attention/advice.

Most important symptoms/effects, acute and delayed

Refer to SECTION 11



Hydraulic Fluid HVI 68

Version 1.01 Revision Date 07.09.2023

SECTION 5. Firefighting measures

Suitable extinguishing

media

Water spray, Foam, CO2, Dry powder.

Special hazards arising from the substance or

mixture

Under conditions of continuous exposure to heat, may burn.
Under extreme conditions (e.g. confinement) could lead to
detonation. Nitrogen oxides (NOx) and carbon oxides are

produced during combustion.

Special protective

equipment for firefighters

Wear self-contained breathing apparatus and protective suit.

SECTION 6. Accidental release measures

Personal precautions Use personal protective equipment. Handle in accordance with

good industrial hygiene and safety practice.

Environmental precautions Prevent further leakage or spillage if safe to do so. Try to

prevent the material from entering drains or water courses.

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid

binder, universal binder, sawdust). Disposal and clean up may

only be done by authorised personnel.

Reference to other sections Refer to section 8 and 13

SECTION 7. Handling and storage

Print Date 07.09.2023 100000006488 5/13



Hydraulic Fluid HVI 68

Version 1.01 Revision Date 07.09.2023

Safe handling advice Wear personal protective equipment. Do not breathe vapours

or spray mist. Avoid contact with skin and eyes. Ensure adequate ventilation. Keep away from flames and sparks.

Advice on protection No data available

against fire and explosion

Requirements for storage Keep away from heat. Do not store near combustible materials.

areas and containers

Advice on common storage No data available

SECTION 8. Exposure controls/personal protection

Components with workplace control parameters

NATIONAL OCCUPATIONAL EXPOSURE LIMITS

Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Respiratory protection In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection Gloves suitable for permanent contact:

Material: butyl-rubber
Break through time: 4 h
Material thickness: 0.5 mm



Hydraulic Fluid HVI 68

Version 1.01 Revision Date 07.09.2023

Eye protection Safety goggles

Skin and body protection lightweight protective clothing

Hygiene measures Wash hands before breaks and immediately after handling the

product.

SECTION 9. Physical and chemical properties

Information on basic physical and chemical properties

Form Liquid

State of matter Liquid; at 20 ° C; 1,013 hPa

Colour Light brown

Odour mild

Odour Threshold No data available

pH No data available

pourpoint -18 ° C

Flash point 230 ° C

Evaporation rate No data available

Flammability (solid, gas) No data available

Auto-ignition temperature > 320 ° C

Lower explosion limit No data available

Upper explosion limit No data available

Vapour pressure No data available



Hydraulic Fluid HVI 68

Version 1.01 Revision Date 07.09.2023

Relative vapour density No data available

Density 0.88 g/cm3; 20 ° C

Water solubility Immiscible

Partition coefficient: n-

octanol/water

No data available

Viscosity, kinematic 70 mm2/s; 40 ° C

SECTION 10. Stability and reactivity

Reactivity Stable under normal conditions.

Chemical stability No data available

Possibility of hazardous

reactions

Strong acids and oxidizing agents

Conditions to avoid No data available

Materials to avoid Combustible material

Hazardous decomposition

Stable under normal conditions.

products

SECTION 11. Toxicological information

Acute oral toxicity Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

LD50 Rat: 5,000 mg/kg;

Print Date 07.09.2023 10000006488 8/13



Hydraulic Fluid HVI 68

Version 1.01 Revision Date 07.09.2023

Acute inhalation toxicity Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

LC50 Rat: 4 h; 2.18 - 5.53 mg/l;

Acute dermal toxicity Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

LD50 Rabbit: 2,000 - 5,000 mg/kg;

Repeated dose toxicity Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

Oral Rat; Lowest observed adverse effect level 125 mg/kg

Repeated dose toxicity Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

Dermal Rat; NOAEL Early embryonic development 30 - 2,000

mg/kg

Repeated dose toxicity Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

Dermal Mouse; NOAEL Early embryonic development 150 mg/kg Lowest observed adverse effect level 100 mg/kg

Repeated dose toxicity Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

Dermal Rabbit; NOAEL Early embryonic development 1,000

mg/kg

Carcinogenicity Mineral oils are severely solvent refined or hydrotreated.

SECTION 12. Ecological information

Toxicity to fish Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

Print Date 07.09.2023 100000006488 9/13



Hydraulic Fluid HVI 68

Version 1.01 Revision Date 07.09.2023

unspecified:

4 d; LL50; 100 mg/l;

Toxicity to daphnia and other

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

aquatic invertebrates

unspecified:

No data available

Toxicity to algae

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

No data available

Toxicity to bacteria

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

No data available

SECTION 13. Disposal considerations

Product Dispose of in accordance with local regulations.

SECTION 14. Transport information

Further Information Not classified as dangerous in the meaning of transport

regulations.

SECTION 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Canada. DSL - Domestic Substances List, Components Not listed

part of CEPA Acrylic copolymer

Mineral Oil

Print Date 07.09.2023 100000006488 10/13



Hydraulic Fluid HVI 68

Version 1.01 Revision Date 07.09.2023

Zinc dialkyl dithiophosphate

Alkyl Phenol (isomer)

Australia. AICS - Australian Inventory of

Chemical Substances

Components Not listed

Acrylic copolymer

Mineral Oil

Zinc dialkyl dithiophosphate

Alkyl Phenol (isomer)

New Zealand Inventory of Chemical

Substances

Components Not listed

Acrylic copolymer

Mineral Oil

Zinc dialkyl dithiophosphate

Alkyl Phenol (isomer)

Japan. ENCS - Existing and New Chemical

Substances Inventory

Components Not listed

Distillates (petroleum), hydrotreated heavy paraffinic

Acrylic copolymer

Mineral Oil

Zinc dialkyl dithiophosphate

Alkyl Phenol (isomer)

Japan. Industrial Safety and Health Law -

Inventory

Components Not listed

Distillates (petroleum), hydrotreated heavy paraffinic

Acrylic copolymer

Mineral Oil

Zinc dialkyl dithiophosphate

Alkyl Phenol (isomer)

Korea. KECI - Korean Existing Chemicals

Inventory

Components Not listed

Acrylic copolymer

Mineral Oil

Print Date 07.09.2023 100000006488 11/13



Hydraulic Fluid HVI 68

Version 1.01 Revision Date 07.09.2023

Zinc dialkyl dithiophosphate

Alkyl Phenol (isomer)

Philippines. PICCS - Philippines Inventory of

Chemicals and Chemical Substances

Components Not listed

Acrylic copolymer

Mineral Oil

Zinc dialkyl dithiophosphate

Alkyl Phenol (isomer)

China. IECSC - Inventory of Existing

Chemical Substances in China

Components Not listed

Acrylic copolymer

Mineral Oil

Zinc dialkyl dithiophosphate

Alkyl Phenol (isomer)

Taiwan. Chemical Substances Inventory

(TCSI)

Components Not listed

Acrylic copolymer

Mineral Oil

Zinc dialkyl dithiophosphate

Alkyl Phenol (isomer)

USA TSCA Inventory Components Not listed

Acrylic copolymer

Mineral Oil

Zinc dialkyl dithiophosphate

Alkyl Phenol (isomer)

SECTION 16. Other information

Full text of H-Statements

H225 Highly flammable liquid and vapour.

Print Date 07.09.2023 10000006488 12/13



Hydraulic Fluid HVI 68

Version 1.01

Revision Date 07.09.2023

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects.

All reasonable efforts were exercised to compile this SDS in accordance with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS). The SDS only provides information regarding the health, safety and environmental hazards at the date of issue, to facilitate the safe receipt, use and handling of this product in the workplace and does not replace any product information or product specifications. Since Sasol and its subsidiaries cannot anticipate or control all conditions under which this product may be handled, used and received in the workplace, it remains the obligation of each user, receiver or handler to, prior to usage, review this SDS in the context within which this product will be received, handled or used in the workplace. The user, handler or receiver must ensure that the necessary mitigating measures are in place with respect to health and safety. This does not substitute the need or requirement for any relevant risk assessments to be conducted. It further remains the responsibility of the receiver, handler or user to communicate such information to all relevant parties that may be involved in the receipt, use or handling of this product.

Although all reasonable efforts were exercised in the compilation of this SDS, Sasol does not expressly warrant the accuracy of, or assume any liability for incomplete information contained herein or any advice given. When this product is sold, risk passes to the purchaser in accordance with the specific terms and conditions of sale.

Print Date 07.09.2023 100000006488 13/13