

# SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Trade name	NOVEL 1412-3 Ethoxylate	
Synonyms	Ethoxylated Alcohol, Laureth-3	
Use	Detergent, Industrial use	
Company	Sasol Chemicals (USA) LLC (an affiliate of Sasol Chemicals North America LLC)	
Address	12120 Wickchester Lane, Houston, TX 77079	
Telephone	CHEMTREC North America Transportation Emergency (24-hr)	(800) 424 9300
	CHEMTREC World Wide	(703) 527-3887
	Other Emergencies (24-hr)	(337) 494 5142
	SDS and Product Information (8:00am-4:30pm CST)	(281) 588 3491
	Health and Safety Information (7:30am-4:00pm CST)	(281) 588 3492
E-mail address	SasolElectronicSDS@us.sasol.com	

### SECTION 2 HAZARDS IDENTIFICATION

OSHA/GHS	Acute toxicity (Oral)	Category 4
Hazards	Serious eye damage	Category 1
	Acute aquatic toxicity	Category 1
	Chronic aquatic toxicity	Category 3

### LABEL ELEMENTS



Signal word Danger

Hazard statements H302 Harmful if swallowed.

- H318 Causes serious eye damage.
  - H400 Very toxic to aquatic life.
  - H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements

PreventionP264Wash skin thoroughly after handling.P270Do not eat, drink or smoke when using this product.



P280	Wear eye protection/ face protection.
------	---------------------------------------

P273 Avoid release to the environment.

P301 + P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Response P330 Rinse mouth. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/doctor. P391 Collect spillage.

#### Disposal P501 Dispose of contents/ container to an approved waste disposal plant.

Additional advice This product may contain residual levels of alcohols which, even under normal handling conditions, may smell and irritate the eyes, nose, and throats of some individuals.

#### **SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS**

## **Components**

Alcohols, C10-16, ethoxylated

Weight percent CAS-No. 68002-97-1 100

See Section 8 for Exposure Guidelines and Section 15 for Regulatory Classifications.

#### **SECTION 4** FIRST AID MEASURES

**Eye contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Wash off immediately with soap and plenty of water while removing all contaminated Skin contact clothes and shoes. When symptoms persist or in all cases of doubt seek medical advice. Wash contaminated clothing before re-use.

- Inhalation Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.
- Ingestion If swallowed, call a poison control centre or doctor immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

#### **SECTION 5** FIREFIGHTING MEASURES

### **FLAMMABLE PROPERTIES**

Fire/explosion NFPA Class IIIB combustible liquid.

**Suitable** Water spray. Foam Dry chemical. Carbon dioxide (CO2).

#### extinguishing media



Protective equipment and precautions for firefighters	Wear self-contained breathing apparatus for firefighting if necessary.
Further information	Keep containers and surroundings cool with water spray. Do not use a solid water stream as it may scatter and spread fire. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

### SECTION 6 ACCIDENTAL RELEASE MEASURES

Methods and<br/>materials for<br/>containment and<br/>cleaning upEvacuate personnel to safe areas. Remove all sources of ignition. Contain spillage, and<br/>then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous<br/>earth, vermiculite) and place in container for disposal according to local / national<br/>regulations (see section 13). Do not flush into surface water or sanitary sewer system.

### SECTION 7 HANDLING AND STORAGE

**Safe handling advice** Take precautionary measures against static discharges.

Storage/Transport pressure	Ambient	
Load/Unload temperature	24 - 38 °C 75 - 100 °F	
Storage and handling materials	Suitable: Carbon steel coated with baked phenolic. Any moisture may cause rusting of carbon steel. If product is moisture free, uncoated carbon steel tanks.	
Further information on storage conditions		

### SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **ENGINEERING MEASURES**

Ensure adequate ventilation, especially in confined areas. Trace amounts of ethylene oxide may be present in the product and could accumulate in vapor spaces of storage or transport vessels.

### PERSONAL PROTECTIVE EQUIPMENT

**Eyes** Wear as appropriate: Goggles. Face-shield.



- **Skin** Full protective clothing, chemical boots, and chemical gloves. High standards of skin care and personal hygiene should be exercised at all times.
- **Inhalation** Use respirator when performing operations involving potential exposure to vapour of the product. Use NIOSH approved respiratory protection.

#### **EXPOSURE GUIDELINES**

There are no exposure limits established for this product. Trace amounts of ethylene oxide may be present in this product., The ethylene oxide in this product is not expected to result in significant exposures or present a health hazard.

### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance	liquid
Colour	Clear to slightly hazy
Form	liquid
Odour	sweet pungent
Odour Threshold	No data available
Flash point	estimated > 204 °C, 399 °F; PM;
Flammability	Upper explosion limit: approximately 1.2 %(V)
	Lower explosion limit: approximately 0.2 %(V)
Boiling point/boiling range	ca. 275 °C, 527 °F;
Melting point/range	8 - 13 °C, 46 - 56 °F;
Auto-ignition temperature	ca. 237 °C, 459 °F;
Decomposition temperature	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Vapour density	10 - 12
Density	0.9263 g/cm3 @ 22 °C, 71.6 °F;



Relative density	No data available
Water solubility	Dispersible
Viscosity	27.2 cSt @ 25 °C, 77 °F;
рН	6.9
Evaporation rate	No data available
Partition coefficient: n- octanol/water	No data available

#### **SECTION 10 STABILITY AND REACTIVITY**

<b>Reactivity</b> Sta	ble at normal ambient temperature and pressure.
-----------------------	---

No decomposition if stored and applied as directed. Chemical stability

Conditions to avoid Reacts slowly with air or oxygen. Storage under heated conditions in the presence of air or oxygen increases reaction rate. For example, after storing at 95°F/35°C for 30 days in the presence of air, there is measureable oxidation of the ethoxylate. Lower temperatures will allow for longer storage time and higher temperatures will shorten the storage time if stored under an air or oxygen atmosphere.

When storing this product in air or oxygen, decomposition may occur, generating vapors Hazardous which could be irritating. Ensure adequate ventilation, especially in confined areas. decomposition Oxidation is not expected when stored under a nitrogen atmosphere. products

Materials to avoid Can react with strong oxidizers, inorganic acids, and halogens.

Hazardous None. polymerisation

#### **TOXICOLOGICAL INFORMATION SECTION 11**

Additional Remarks	Information given is based on data obtained from similar substances.
Acute dermal toxicity	LD50: > 2,000 mg/kg Category approach
Acute inhalation toxicity	LC50 value expected to exceed the saturated vapor concentration in air.
Acute oral toxicity	LD50: > 300 - 2,000 mg/kg Category approach

### SAFETY DATA SHEET



## NOVEL 1412-3 Ethoxylate

Harmful if swallowed.

Skin corrosion/irritation	Primary irritation (Rabbit): 24 hours; 2.0 (Max. score is 8.0.)
Serious eye damage/eye irritation	Primary irritation (Rabbit): 22.8 (Max. score is 110.) Test substance: NOVEL 1214GC-3 Ethoxylate Causes serious eye damage.
Respiratory or skin sensitisation	No data available
Germ cell mutagenicity	Genotoxicity in vitro: No data available
	Genotoxicity in vivo: No data available
	Assessment Mutagenicity: No data available
Reproductive toxicity	Reproductive toxicity: No data available
	Assessment Reproductive toxicity: No data available
	Teratogenicity: No data available
	Assessment teratogenicity: No data available
STOT - single exposure	No data available
STOT - repeated exposure	No data available
Aspiration toxicity	No data available
Carcinogenicity	<b>Assessment carcinogenicity:</b> No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.



### SECTION 12 ECOLOGICAL INFORMATION

Aquatic toxicity	Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.	
Toxicity to fish	EC50 (Cyprinus carpio (Carp)) 72 hours: 0.8 mg/l Test substance: C1214-3 Ethoxylate	
	LC50 (Daphnia magna (Water flea)) 48 hours: 0.8 mg/l Test substance: C1214-3 Ethoxylate	
Toxicity to algae	<ul> <li>ErC50 (Desmodesmus subspicatus (green algae)) 72 hours: 0.5 mg/l</li> <li>Test substance: C1214-3 Ethoxylate</li> </ul>	
	EC10 (Scenedesmus) 72 hours: > 0.1 - 1 mg/l Category approach	
Chronic toxicity to fish	No data available	
Chronic toxicity to aquatic invertebrates	No data available	
Biodegradation	Readily biodegradable. OECD Test Guideline 301A (28 d): > 70 % Test substance: C1214-3 Ethoxylate	
Bioaccumulative potential	No data available	
Mobility in soil	No data available	
Other adverse effects	No data available	

### SECTION 13 DISPOSAL CONSIDERATIONS

**Waste Code** Any unused product or empty containers may be disposed of as non-hazardous in accordance with state and federal requirements. Re-evaluation of the product may be required by the user at the time of disposal, since the product uses, transformations, mixtures, contamination, and spillage may change the classification. If the resulting material is determined to be hazardous, please dispose in accordance with state and federal (40 CFR 262) hazardous waste regulations.

**Disposal methods** Dispose of only in accordance with local, state, and federal regulations.



**Empty containers.** Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, triple-rinsed, properly bunged and promptly returned to a drum reconditioner, or properly disposed.

### SECTION 14 TRANSPORT INFORMATION

- **DOT** UN 3082, Environmentally hazardous substance, liquid, n.o.s., (Alcohol C12-16 poly (1-6) ethoxylate), 9, III, Marine pollutant Not regulated in non-bulk packaging of 119 gallons or less or a net mass of 882 pounds or less per package.
- IATA UN 3082, Environmentally hazardous substance, liquid, n.o.s., (Alcohol C12-16 poly (1-6) ethoxylate), 9, III
   Not regulated in non-bulk packaging of 5L or less or a net mass of 5kg or less per package.
- **IMDG** UN 3082, Environmentally hazardous substance, liquid, n.o.s., (Alcohol C12-16 poly (1-6) ethoxylate), 9, III, Marine pollutant This product is regulated as a Marine Pollutant when shipped by water in all quantities according to the IMDG Code.

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks No data available

### SECTION 15 REGULATORY INFORMATION

### **U.S. FEDERAL REGULATIONS**

### **TSCA Inventory Listing**

ComponentsCAS-No.Alcohols, C10-16, ethoxylated68002-97-1All chemical substances in this product are either on the TSCA Active Inventory, or in compliance with the inventory.

### SARA 302 Status

Components

CAS-No.

Weight percent

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### SARA 311/312 Classification

Should this product meet EPCRA 311/312 Tier reporting criteria of 40 CFR 370, refer to Section 2 of this SDS for appropriate classification and Section 3 for components that meet the hazardous classification.

### SARA 313 Chemical

### **Components**

CAS-No. Weight percent This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### US. EPA CERCLA Hazardous Substances (40 CFR 302) Components

none

**Reportable Quantity** 

Weight percent

### INTERNATIONAL REGULATIONS

WHMIS CI	assification
----------	--------------

Acute toxicity (Oral)	Category 4
Serious eye damage	Category 1
Acute aquatic toxicity	Category 1
Chronic aquatic toxicity	Category 3

### **European Union**

This surfactant complies with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Classification according to Regulation (EU) 1272/2008.

Serious eye damage, Category 1 Acute toxicity (Oral), Category 4 Acute aquatic toxicity, Category 1 Chronic aquatic toxicity, Category 3

Australia. Inventory of Chemical Substances (AICS)	Listed
Japan. Inventory of Existing and New Chemical Substances (ENCS)	Listed
Japan. ISHL - Inventory of Chemical Substances	Listed
Canada. Domestic Substances List (DSL) Inventory	Listed
Canada. Non-Domestic Substance Listing (NDSL)	Not listed
Philippines. Inventory of Chemicals / Chemical Substances (PICCS)	Listed
Korea. Existing Chemicals Inventory (KECI)	Listed



Sasol



Mexico. National Inventory of Chemical Substances (INSQ)	Not listed
New Zealand. Inventory of Chemical Substances (NZIoC)	Listed
Switzerland. Inventory of Notified New Substances (CHINV)	Listed
Taiwan. National Existing Chemical Inventory (NECI)	Listed

Please note: The names and CAS numbers which are used for this product in the stated inventories may deviate from the information which is listed in Section 3.

### STATE REGULATIONS

California Prop. 65 <u>Components</u> Ethylene Oxide

Sasol Chemicals (USA) LLC's ethoxylates may contain detectable quantities of ethylene oxide which is a chemical on the California Proposition 65 list. The level is typically below 1.0 ppm, although it may vary. The manufacturing process is controlled to reduce the residual ethylene oxide content.

### SECTION 16 OTHER INFORMATION

#### HAZARD RATINGS

			<u>Physical Hazard/</u>
	<u>Health</u>	Flammability	Instability
HMIS®	3	1	0
NFPA	3	1	0

THE DATA AND INFORMATION CONTAINED HEREIN ARE BEING FURNISHED FOR INFORMATIONAL PURPOSES ONLY, UPON THE EXPRESS CONDITION THAT EACH CUSTOMER SHALL MAKE ITS OWN ASSESSMENT OF APPROPRIATE USE AND APPROPRIATE SHIPPING, TRANSFER AND STORAGE MATERIALS AND PROCEDURES FOR SASOL CHEMICALS (USA) LLC'S PRODUCTS. ALTHOUGH BASED ON INFORMATION SOURCES WHICH SASOL CHEMICALS (USA) LLC CONSIDERS ACCURATE AND RELIABLE, SASOL CHEMICALS (USA) LLC MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE VALIDITY OF THIS INFORMATION, THE INFORMATION SOURCES UPON WHICH THE SAME ARE BASED, OR THE RESULTS TO BE OBTAINED, AND EXPRESSLY DISCLAIMS LIABILITIES FOR DAMAGES OR INJURIES RESULTING FROM THE USE THEREOF.

. . . .

CAS-No.

75-21-8