

### n-Propanol

Version 1.00

Revision Date 08.09.2021

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

| Product identifier                 |   |  |
|------------------------------------|---|--|
| Trade name                         | n-Propanol  |  |
| Synonyms                           | 1-Propanol, Hydroxypropane, 1-Propyl alcohol, Ethyl carbinol,<br>n-Propan-1-ol, n-Propyl alcohol. |  |
| Product code                       | 2044  |  |
| CAS-No.                            | 71-23-8   |  |
| Relevant identified uses of the su | bstance or mixture and uses advised against   |  |
| Use                                | Solvent. Industrial use.  |  |
| Manufacturer or supplier's details |   |  |
| Company                            | Sasol Chemicals, a division of Sasol South Africa Ltd   |  |
| Address                            | Sasol Place, 50 Katherine Street<br>Sandton<br>2090<br>Souith Africa<br>+27103445000              |  |
| Telephone                          |   |  |
| E-mail address                     | sasolchem.info.sa@sasol.com   |  |
| Emergency telephone number         | +44 (0)1235 239 670 (Europe, Israel, Africa, Americas)  |  |
|                                    | +44(0)1235 239 671 (Middle East, Arabic African countries)  |  |
|                                    | +65 3158 1074 (Asia Pacific)  |  |
|                                    | +86 400 120 6011 (China)  |  |
|                                    | +27 (0)17 610 4444 (South Africa)   |  |
|                                    | 0800 112 890 RSA-Local only   |  |
|                                    | +61 (2) 8014 4558 (Australia)   |  |

### **SECTION 2. Hazards identification**

#### Classification of the substance or mixture

| GHS Classification    |   |                     |
|-----------------------|---|---------------------|
|                       | Globally Harmonized System of Classification<br>Chemicals (GHS) | on and Labelling of |
|                       | Flammable liquids   | Category 3          |
| Classification        | Serious eye damage/eye irritation                               | Category 1          |
|                       | Specific target organ toxicity - single exposure                | Category 3          |
| GHS label elements    |   |                     |
| Print Date 08.09.2021 | 10000000473   | 1/10                |



| <b>n-Propanol</b><br>Version 1.00 | Revision Date 08.09.2021  |
|-----------------------------------|---|
| Hazard pictograms                 |   |
| Signal word                       | : Danger  |
| Hazard statements                 | <ul> <li>H226Flammable liquid and vapour.</li> <li>H318Causes serious eye damage.</li> <li>H336May cause drowsiness or dizziness.</li> </ul>  |
| Precautionary statements          | <ul> <li>Prevention:</li> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P233 Keep container tightly closed.</li> <li>P240 Ground and bond container and receiving equipment.</li> <li>P241 Use explosion-proof electrical/ ventilating/ lighting equipment.</li> <li>P242 Use non-sparking tools.</li> <li>P243 Take action to prevent static discharges.</li> <li>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</li> </ul> |
|                                   | Response:<br>P370 + P378 In case of fire: Use dry sand, dry chemical or<br>alcohol-resistant foam to extinguish.<br>P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with<br>water for several minutes. Remove contact lenses, if present<br>and easy to do. Continue rinsing. Immediately call a POISON<br>CENTER or doctor/ physician.<br>P304 + P340 IF INHALED: Remove person to fresh air and<br>keep comfortable for breathing.   |
|                                   | <b>Storage:</b><br>P403 + P235 Store in a well-ventilated place. Keep cool.   |
|                                   | <b>Disposal:</b><br>P501 Dispose of contents/ container to an approved waste<br>disposal plant.   |

#### Other hazards which do not result in classification

• None known.



#### n-Propanol

Version 1.00

Revision Date 08.09.2021

#### **SECTION 3. Composition/information on ingredients**

#### Substance

Propan-1-ol

Contents: 99.90 %W/W CAS-No. 71-23-8

# Index-No. 603-003-00-0 EC-No. 200-746-9 Hazard statements H225 H318 H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4. First aid measures**

#### **Description of necessary first-aid measures**

| Inhalation   | Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.                                   |
|--------------|---|
| Skin contact | Wash off immediately with soap and plenty of water while<br>removing all contaminated clothes and shoes. Wash<br>contaminated clothing before re-use. If skin irritation persists,<br>call a physician. |
| Eye contact  | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.  |
| Ingestion    | If swallowed, seek medical advice immediately and show this<br>container or label. Do not induce vomiting without medical<br>advice. Never give anything by mouth to an unconscious<br>person.          |
|              |   |

Most important symptoms/effects, acute and delayed

Refer to SECTION 11

### **SECTION 5. Firefighting measures**

| Suitable extinguishing media                                | Water spray. Alcohol-resistant foam. Dry chemical. Carbon dioxide.                            |
|---|---|
| Unsuitable extinguishing media                              | No information available.   |
| Special hazards arising<br>from the substance or<br>mixture | Flash back possible over considerable distance. Vapours may form explosive mixtures with air. |



#### n-Propanol

Version 1.00

Revision Date 08.09.2021

Special protective equipment for firefighters

Wear self-contained breathing apparatus and protective suit.

#### **SECTION 6.** Accidental release measures

| Personal precautions         | Keep people away from and upwind of spill/leak. Remove all sources of ignition. Do not breathe vapours or spray mist. Ensure adequate ventilation.  |
|------------------------------|---|
| Environmental<br>precautions | Should not be released into the environment. Prevent further<br>leakage or spillage if safe to do so. Do not allow material to<br>contaminate ground water system. Do not flush into surface<br>water or sanitary sewer system. |
| Methods for cleaning up      | Soak up with inert absorbent material and dispose of as hazardous waste.  |
| Reference to other sections  | Refer toSection8and13   |

### **SECTION 7. Handling and storage**

| Safe handling advice                            | Provide sufficient air exchange and/or exhaust in work rooms.<br>Wear personal protective equipment. Take precautionary<br>measures against static discharges. Ensure all equipment is<br>electrically grounded before beginning transfer operations. |  |
|---|---|--|
| Advice on protection against fire and explosion | Keep away from open flames, hot surfaces and sources of ignition.Use explosion-proof equipment.   |  |
| Temperature class                               | T1  |  |
| Requirements for storage areas and containers   | Keep container tightly closed in a dry and well-ventilated place.Keep away from heat.Keep away from direct sunlight.  |  |
| Advice on common storage                        | Keep containers tightly closed in a cool, well-ventilated place.  |  |

#### **SECTION 8. Exposure controls/personal protection**

#### Components with workplace control parameters

#### NATIONAL OCCUPATIONAL EXPOSURE LIMITS

| parameters | Components | Туре | Control | Update | Basis |
|------------|------------|------|---------|--------|-------|
|------------|------------|------|---------|--------|-------|



### n-Propanol

Version 1.00

#### Revision Date 08.09.2021

| N-PROPANOL (ALCOHOL | CMP     | 200 ppm | 2003 | Argentina OELs |
|---------------------|---------|---------|------|----------------|
| N-PROPÍLICO)        | CMP CPT | 250 ppm | 2003 | Argentina OELs |
| N-PROPANOL (ALCOHOL |         |         |      | _              |
| N-PROPÍLICO)        |         |         |      |                |
| N-PROPANOL (ALCOHOL |         |         |      |                |
| N-PROPÍLICO)        |         |         |      |                |

#### **Exposure controls**

#### Engineering measures

Provide sufficient air exchange and/or exhaust in work rooms.

#### Personal protective equipment

| Respiratory protection   | In case of insufficient ventilation, wear suitable respiratory equipment.   |
|--------------------------|---|
| Hand protection          | Gloves suitable for permanent contact:<br>Material: butyl-rubber<br>Break through time: 4 h<br>Material thickness: 0.5 mm<br>Safety glasses with side-shields |
| Lye protection           | Salety glasses with side-shields  |
| Skin and body protection | Protective suit. Safety shoes   |
| Hygiene measures         | Wash hands before breaks and immediately after handling the product. Take off all contaminated clothing immediately.  |

### **SECTION 9.** Physical and chemical properties

#### Information on basic physical and chemical properties

| Form                           | Liquid                      |
|--------------------------------|-----------------------------|
| State of matter                | Liquid; at 20 °C; 1,013 hPa |
| Colour                         | Colourless                  |
| Odour                          | Alcohol-like                |
| Odour Threshold                | No data available           |
| рН                             | 7                           |
| Melting point/range            | -126.2 °C                   |
| Boiling point/boiling<br>range | 97.2 °C                     |
| Flash point                    | 26 °C; closed cup           |
| Evaporation rate               | No data available           |
| Flammability (solid, gas)      | No data available           |
| Auto-ignition temperature      | 371 °C                      |



#### n-Propanol

Version 1.00

Revision Date 08.09.2021 Decomposition No data available Temperature Lower explosion limit 2.1 %(V) **Upper explosion limit** 13.5 %(V) Vapour pressure 27.998 hPa; 25 °C **Relative vapour density** 2.1 Density 0.805 g/cm3; 20 °C Water solubility Completely miscible Partition coefficient: n-No data available octanol/water Viscosity, dynamic 2.170 mPa.s; 40 °C

### **SECTION 10. Stability and reactivity**

| Reactivity                            | Stable under recommended storage conditions.                           |
|---------------------------------------|--|
| Chemical stability                    | Stable under recommended storage conditions.                           |
| Possibility of hazardous<br>reactions | Hazardous polymerisation does not occur.                               |
| Conditions to avoid                   | Extremes of temperature and direct sunlight. Heat, flames and sparks.  |
| Materials to avoid                    | Strong oxidizing agents Incompatible with acids. Halogenated compounds |
| Hazardous<br>decomposition products   | Carbon oxides  |

### **SECTION 11. Toxicological information**

| Acute oral toxicity       | Propan-1-ol:<br>LD50 Oral : > 2,000 mg/kg;  (literature value)                                     |
|---------------------------|--|
| Acute oral toxicity       | Butan-2-ol:<br>LD50 Oral Rat: male2,054 mg/kg;  (literature value)                                 |
| Acute inhalation toxicity | Propan-1-ol:<br>LC50 Rat: male and female; 4 h; vapour; 13548 ppm; GLP:<br>yes; (literature value) |
| Acute dermal toxicity     | Propan-1-ol:<br>LD50 Dermal Rabbit: male; 6,730 mg/kg; (literature value)                          |
| Skin irritation           | Propan-1-ol:<br>Rabbit: Not irritating; Draize Test (literature value)                             |
| Eye irritation            | Propan-1-ol:   |
| Print Date 08.09.2021     | 10000000473  |



**Mutagenicity** 

#### n-Propanol

Version 1.00

Revision Date 08.09.2021

Rabbit: Highly irritating 24 - 72 h; (literature value) Propan-1-ol: Ames test: Salmonella typhimurium; Not mutagenic; (literature value)

### **SECTION 12. Ecological information**

| Toxicity to fish                                    | Propan-1-ol:<br>static test; Pimephales promelas; 96 h; LC50; 4,650 mg/l; GLP:<br>no; (literature value)   |
|---|--|
| Toxicity to daphnia and other aquatic invertebrates | Propan-1-ol:<br>static test; Daphnia magna (Water flea); 48 h; EC50; 3,644<br>mg/l(literature value)   |
| Biodegradability                                    | Propan-1-ol:<br>aerobic; 3 mg/l; 81 %; 20 d; Readily biodegradable.; (literature<br>value)   |
| Mobility in soil                                    | No data available  |
| Results of PBT and vPvB assessment                  | This substance is not considered to be persistent,<br>bioaccumulating and toxic (PBT). This substance is not<br>considered to be very persistent and very bioaccumulating<br>(vPvB). |

### **SECTION 13. Disposal considerations**

| Product   | In accordance with local and national regulations. Do not<br>contaminate ponds, waterways or ditches with chemical or<br>used container. The product should not be allowed to enter<br>drains, water courses or the soil. |
|-----------|---|
| Packaging | Dispose of spent product packaging responsibly and lawfully with due consideration for health, safety and the environment.  |

### **SECTION 14. Transport information**

**DG Pictogram** 





### n-Propanol

| Version 1.00  | Revision Date 08.09.2021                            |
|---|---|
| UN number:  | 1274  |
| Class:  | 3   |
| Packaging group:  | III; F1;  |
| Proper shipping name:   | n-PROPANOL  |
| RID   |   |
| UN number:  | 1274  |
| Class:  | 3   |
| Packaging group:  | III; F1   |
| Proper shipping name:   | n-PROPANOL  |
| ADNR  |   |
| UN number:  | 1274  |
| Class:  | 3   |
| Packaging group:  | III; F1   |
| Proper shipping name:   | n-PROPANOL  |
| IMDG  |   |
| UN number:  | 1274  |
| Class:  | 3   |
| EmS:  | F-E, S-D  |
| Packaging group:  | III   |
| Proper shipping name:   | n-PROPANOL  |
| Marine pollutant  | Not a Marine Pollutant                              |
| ICAO/IATA   |   |
| UN number :   | 1274  |
| Class:  | 3   |
| Packaging group:  | III   |
| Proper shipping name:   | n-PROPANOL  |
| Transport in bulk<br>according to Annex II of<br>MARPOL 73/78 and the<br>IBC Code | n-Propanol<br>Pollution Category: Y<br>Ship Type: 3 |

# SECTION 15. Regulatory information



#### n-Propanol

Version 1.00

Revision Date 08.09.2021

| Safety, health and environmental regulations/legislation specific for the substance or mixtureUSA TSCA InventoryAll chemical constituents are listed in: USA TSCA Inventory<br>(See chapter 3) |   |  |
|--|---|--|
| Canadian Domestic Substances List (DSL)  | All chemical constituents are listed in: Canadian Domestic Substances List (DSL) (See chapter 3)                            |  |
| Australian Inv. of Chem. Substances<br>(AICS)  | All chemical constituents are listed in: Australian Inv. of Chem.<br>Substances (AICS) (See chapter 3)                      |  |
| New Zealand Inventory of Chemicals (NZIoC)   | All chemical constituents are listed in: New Zealand Inventory of Chemicals (NZIoC) (See chapter 3)                         |  |
| Jap. Inv. of Exist. & New Chemicals<br>(ENCS)  | All chemical constituents are listed in: Jap. Inv. of Exist. & New Chemicals (ENCS) (See chapter 3)                         |  |
| Japan. Industrial Safety & Health Law<br>(ISHL)  | All chemical constituents are listed in: Japan. Industrial Safety & Health Law (ISHL) (See chapter 3)                       |  |
| Korea. Existing Chemicals Inventory<br>(KECI)  | All chemical constituents are listed in: Korea. Existing Chemicals Inventory (KECI) (See chapter 3)                         |  |
| Philippines Inventory of Chemicals and<br>Chemical Substances (PICCS)  | All chemical constituents are listed in: Philippines Inventory of Chemicals and Chemical Substances (PICCS) (See chapter 3) |  |
| China Inv. Existing Chemical Substances (IECSC)  | All chemical constituents are listed in: China Inv. Existing Chemical Substances (IECSC) (See chapter 3)                    |  |

#### **SECTION 16.** Other information

#### Full text of H-Statements

H225 Highly flammable liquid and vapour.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

All reasonable efforts were exercised to compile this SDS in accordance with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS). The SDS only provides information regarding the health, safety and environmental hazards at the date of issue, to facilitate the safe receipt, use and handling of this product in the workplace and does not replace any product information or product specifications. Since Sasol and its subsidiaries cannot anticipate or control all conditions under which this product may be handled, used and received in the workplace, it remains the obligation of each user, receiver or handler to, prior to usage, review this SDS in the context within which this product will be received, handled or used in the workplace. The user, handler or receiver must ensure that the necessary mitigating measures are in place with respect to health and safety. This does not substitute the need or requirement for any relevant risk assessments to be conducted. It further remains the responsibility of the receiver, handler or user to communicate such information to all relevant parties that may be involved in the receipt, use or handling of this product.

Although all reasonable efforts were exercised in the compilation of this SDS, Sasol does not expressly warrant the accuracy of, or assume any liability for incomplete information contained herein or any advice given. When this product is sold, risk passes to the purchaser in accordance with the specific terms and conditions of sale.



### n-Propanol

Version 1.00

Revision Date 08.09.2021