

Safety Data Sheet

Circulating and Gear Oil 150

Version 1.01

Revision Date 29.08.2023

SECTION 1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name Circulating and Gear Oil 150

Relevant identified uses of the substance or mixture and uses advised against

Use Lubricant or lubricant additive

Manufacturer or supplier's details

Company Sasol Oil Pty (Ltd)
Address Sasol Place, 50 Katherine Street
Sandton
2090
South Africa

Telephone +27860335444

E-mail address sasolchem.info.sa@sasol.com

Emergency telephone number South Africa: 0800 11 28 90; International: +27 17 610 4444

SECTION 2. Hazards identification

Classification of the substance or mixture

REGULATION (EC) No 1272/2008

Classification Skin sensitisation Category 1

Label elements

Hazard pictograms



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Safety Data Sheet

Circulating and Gear Oil 150

Version 1.01

Revision Date 29.08.2023

Precautionary statements

Prevention

P261 Avoid breathing mist or vapours or spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P317 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage

Disposal

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3. Composition/information on ingredients

Mixture

Base Oil

Contents: <= 99.30 %W/W

CAS-No.

Index-No.

EC-No.

Hydrocarbons, C10-C13, aromatics, <1% naphthalene

Contents: >= 0.12 - <= 0.16 %W/W

CAS-No.

Index-No.

EC-No.

Hazard statements H304 H411

Safety Data Sheet

Circulating and Gear Oil 150

Version 1.01

Revision Date 29.08.2023

N-1-naphthylaniline

Contents: ≥ 0.07 - ≤ 0.11 %W/W

CAS-No. 90-30-2

Index-No.

EC-No. 201-983-0

Hazard statements *H302 H317 H373 H400 H410*

Long-chain alkenyl amide

Contents: ≥ 0.05 - ≤ 0.07 %W/W

CAS-No.

Index-No.

EC-No.

Hazard statements *H315 H361 H413*



sasol

Safety Data Sheet

Circulating and Gear Oil 150

Version 1.01

Revision Date 29.08.2023

SECTION 4. First aid measures

Description of necessary first-aid measures

Inhalation	Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If breathing is difficult, give oxygen. Get medical attention/advice if you feel unwell.
Skin contact	Wash off immediately with soap and plenty of water. Wash contaminated clothing before reuse. Get medical attention if irritation develops and persists.
Eye contact	Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek immediate medical attention/advice.
Ingestion	Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Seek immediate medical attention/advice.

Most important symptoms/effects, acute and delayed

Refer to SECTION 11

SECTION 5. Firefighting measures

Suitable extinguishing media	Water spray, Foam, CO2, Dry powder.
Special hazards arising from the substance or mixture	Under conditions of continuous exposure to heat, may burn. Under extreme conditions (e.g. confinement) could lead to detonation. Nitrogen oxides (NOx) and carbon oxides are produced during combustion.
Special protective equipment for firefighters	Wear self-contained breathing apparatus and protective suit.

SECTION 6. Accidental release measures

Safety Data Sheet

Circulating and Gear Oil 150

Version 1.01

Revision Date 29.08.2023

Personal precautions	Use personal protective equipment. Handle in accordance with good industrial hygiene and safety practice.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Try to prevent the material from entering drains or water courses.
Methods for cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Disposal and clean up may only be done by authorised personnel.

Reference to other sections Refer to section 8 and 13

SECTION 7. Handling and storage

Safe handling advice	Wear personal protective equipment. Do not breathe vapours or spray mist. Avoid contact with skin and eyes. Ensure adequate ventilation. Keep away from flames and sparks.
Advice on protection against fire and explosion	No data available.
Requirements for storage areas and containers	Keep away from heat. Do not store near combustible materials.
Advice on common storage	No data available.

SECTION 8. Exposure controls/personal protection

Components with workplace control parameters

NATIONAL OCCUPATIONAL EXPOSURE LIMITS

Contains no substances with occupational exposure limit values.

Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Safety Data Sheet

Circulating and Gear Oil 150

Version 1.01

Revision Date 29.08.2023

Personal protective equipment

Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Hand protection	<p>Gloves suitable for permanent contact.:</p> <p>Material: nitrile rubber/nitrile latex, PVC or other plastic material gloves, Neoprene</p> <p>Break through time: > 8 h</p> <p>Material thickness: 0.35 mm</p> <p>gloves suitable for splash protection:</p> <p>Material: natural rubber/natural latex</p> <p>Break through time: >= 480 min</p> <p>Material thickness: 0.35 mm</p> <p>Unsuitable gloves</p> <p>Material: butyl-rubber</p>
Eye protection	Safety goggles
Skin and body protection	lightweight protective clothing
Hygiene measures	Wash hands before breaks and immediately after handling the product.

SECTION 9. Physical and chemical properties

Information on basic physical and chemical properties

Form	Liquid
State of matter	Liquid; at 20 ° C; 1,013 hPa
Colour	light brown
Odour	Hydrocarbon-like
Odour Threshold	No data available.
pH	No data available.
Pour point	-15 ° C
Initial boiling point and boiling range	> 280 ° C; No data available.
Flash point	> 260 ° C
Evaporation rate	No data available.

Safety Data Sheet

Circulating and Gear Oil 150

Version 1.01

Revision Date 29.08.2023

Flammability (solid, gas)	No data available.
Auto-ignition temperature	> 320 ° C
Lower explosion limit	typ. 10 %(V)
Upper explosion limit	typ. 1 %(V)
Vapour pressure	< 0.005 hPa
Relative vapour density	No data available.
Density	0.89 g/cm ³ ; 20 ° C
Water solubility	negligible
Partition coefficient: n-octanol/water	No data available.
Viscosity, kinematic	162 mm ² /s; 40 ° C

SECTION 10. Stability and reactivity

Reactivity	Stable under normal conditions.
Chemical stability	No data available.
Possibility of hazardous reactions	Strong acids and oxidizing agents
Conditions to avoid	No data available.
Materials to avoid	Combustible material
Hazardous decomposition products	Stable under normal conditions.

SECTION 11. Toxicological information

Acute oral toxicity	No data available.
Acute inhalation toxicity	No data available.
Acute dermal toxicity	No data available.
Carcinogenicity	Mineral oils are severely solvent refined or hydrotreated.
Further Information	No data available.

SECTION 12. Ecological information

Toxicity to fish	No data available.
Toxicity to bacteria	No data available.



Safety Data Sheet

Circulating and Gear Oil 150

Version 1.01

Revision Date 29.08.2023

Other adverse effects

No data available.

SECTION 13. Disposal considerations

Product

Dispose of in accordance with local regulations.

Packaging

Dispose of spent product packaging responsibly and lawfully with due consideration for health, safety and the environment.

SECTION 14. Transport information

Further Information

Not classified as dangerous in the meaning of transport regulations.

SECTION 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Canada. DSL - Domestic Substances List,
part of CEPA

Components Not listed

Base Oil

Hydrocarbons, C10-C13, aromatics, <1% naphthalene

Long-chain alkenyl amide

Australia. AICS - Australian Inventory of
Chemical Substances

Components Not listed

Base Oil

Hydrocarbons, C10-C13, aromatics, <1% naphthalene

Long-chain alkenyl amide

New Zealand Inventory of Chemical
Substances

Components Not listed

Base Oil

Hydrocarbons, C10-C13, aromatics, <1% naphthalene

Long-chain alkenyl amide

Japan. ENCS - Existing and New Chemical
Substances Inventory

Components Not listed

Base Oil

Safety Data Sheet

Circulating and Gear Oil 150

Version 1.01

Revision Date 29.08.2023

Hydrocarbons, C10-C13, aromatics, <1% naphthalene
Long-chain alkenyl amide

Japan. Industrial Safety and Health Law - Inventory

Components Not listed

Base Oil
Hydrocarbons, C10-C13, aromatics, <1% naphthalene
Long-chain alkenyl amide

Korea. KECI - Korean Existing Chemicals Inventory

Components Not listed

Base Oil
Hydrocarbons, C10-C13, aromatics, <1% naphthalene
Long-chain alkenyl amide

Philippines. PICCS - Philippines Inventory of Chemicals and Chemical Substances

Components Not listed

Base Oil
Hydrocarbons, C10-C13, aromatics, <1% naphthalene
Long-chain alkenyl amide

China. IECSC - Inventory of Existing Chemical Substances in China

Components Not listed

Base Oil
Hydrocarbons, C10-C13, aromatics, <1% naphthalene
Long-chain alkenyl amide

Taiwan. Chemical Substances Inventory (TCSI)

Components Not listed

Base Oil
Hydrocarbons, C10-C13, aromatics, <1% naphthalene
Long-chain alkenyl amide

USA TSCA Inventory

Components Not listed

Base Oil
Hydrocarbons, C10-C13, aromatics, <1% naphthalene
Long-chain alkenyl amide

SECTION 16. Other information

Full text of H-Statements

H302 Harmful if swallowed.

Safety Data Sheet

Circulating and Gear Oil 150

Version 1.01

Revision Date 29.08.2023

- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure if swallowed.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

All reasonable efforts were exercised to compile this SDS in accordance with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS). The SDS only provides information regarding the health, safety and environmental hazards at the date of issue, to facilitate the safe receipt, use and handling of this product in the workplace and does not replace any product information or product specifications. Since Sasol and its subsidiaries cannot anticipate or control all conditions under which this product may be handled, used and received in the workplace, it remains the obligation of each user, receiver or handler to, prior to usage, review this SDS in the context within which this product will be received, handled or used in the workplace. The user, handler or receiver must ensure that the necessary mitigating measures are in place with respect to health and safety. This does not substitute the need or requirement for any relevant risk assessments to be conducted. It further remains the responsibility of the receiver, handler or user to communicate such information to all relevant parties that may be involved in the receipt, use or handling of this product.

Although all reasonable efforts were exercised in the compilation of this SDS, Sasol does not expressly warrant the accuracy of, or assume any liability for incomplete information contained herein or any advice given. When this product is sold, risk passes to the purchaser in accordance with the specific terms and conditions of sale.