

Hydraulic Fluid 46

Version 1.01 Revision Date 26.06.2023

SECTION 1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Telephone

Hydraulic Fluid 46 Trade name

Hydraulic Oil **Synonyms**

Relevant identified uses of the substance or mixture and uses advised against

Use Lubricant or lubricant additive

Manufacturer or supplier's details

Sasol Oil Pty (Ltd) Company

Sasol Place, 50 Katherine Street Address

Sandton 2090

South Africa +27860335444

E-mail address sasolchem.info.sa@sasol.com

Emergency telephone number +44 (0)1235 239 670 (Europe, Israel, Africa, Americas)

+44(0)1235 239 671 (Middle East, Arabic African countries)

+65 3158 1074 (Asia Pacific)

+86 10 5100 3039 (China)

+27 (0)17 610 4444 (South Africa)

+61 (2) 8014 4558 (Australia)



Hydraulic Fluid 46

Version 1.01 Revision Date 26.06.2023

SECTION 2. Hazards identification

Classification of the substance or mixture

REGULATION (EC) No 1272/2008

Classification This substance is not classified as hazardous according to GHS.

Label elements

Pictogram Not applicable

Signal word Not applicable

Hazard statements This substance is not classified as hazardous according to GHS.

Precautionary statements

Prevention No precautionary statement

Response No precautionary statement

Storage No special storage conditions required.

Disposal P501Dispose of contents/container to an approved facility in

accordance with local, regional, national and international regulations.

Other hazards No data available

SECTION 3. Composition/information on ingredients

Print Date 26.06.2023 100000006523 2/12



Hydraulic Fluid 46

Version 1.01 Revision Date 26.06.2023

Mixture

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified

Contents: 99.00 %W/W

CAS-No. 64742-54-7 **Index-No**. 649-467-00-8 **EC-No**. 265-157-1

Hazard statements H304

Mineral Oil

Contents: >= 0.12 - <= 0.21 %W/W

CAS-No. Index-No. EC-No.

Hazard statements H304

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts

Contents: >= 0.26 - <= 0.50 %W/W

CAS-No. 68649-42-3 Index-No. EC-No. 272-028-3

Hazard statements H315 H319 H318 H411

Alkyl Phenol (isomer)

Contents: >= 0.09 - <= 0.17 %W/W

CAS-No. Index-No. EC-No.

Hazard statements H315 H400 H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4. First aid measures

Description of necessary first-aid measures

Print Date 26.06.2023 100000006523 3/12



Hydraulic Fluid 46

Version 1.01 Revision Date 26.06.2023

Inhalation Move to fresh air in case of accidental inhalation of vapours. If

breathing is irregular or stopped, administer artificial

respiration. If breathing is difficult, give oxygen. Get medical

attention/advice if you feel unwell.

Skin contact Wash off immediately with soap and plenty of water. Wash

contaminated clothing before reuse. Get medical attention if

irritation develops and persists.

Eye contact Remove contact lenses. Rinse immediately with plenty of

water, also under the eyelids, for at least 15 minutes. Seek

immediate medical attention/advice.

Ingestion Do not induce vomiting without medical advice. Never give

anything by mouth to an unconscious person. Seek immediate

medical attention/advice.

Most important symptoms/effects, acute and delayed

Refer to SECTION 11

SECTION 5. Firefighting measures

Suitable extinguishing

media

Water spray, Foam, CO2, Dry powder.

Special hazards arising

from the substance or

mixture

Under conditions of continuous exposure to heat, may burn.
Under extreme conditions (e.g. confinement) could lead to
detonation. Nitrogen oxides (NOx) and carbon oxides are

produced during combustion.



Hydraulic Fluid 46

Version 1.01 Revision Date 26.06.2023

Special protective

Wear self-contained breathing apparatus and protective suit.

equipment for firefighters

SECTION 6. Accidental release measures

good industrial hygiene and safety practice.

Environmental precautions Prevent further leakage or spillage if safe to do so. Try to

prevent the material from entering drains or water courses.

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid

binder, universal binder, sawdust). Disposal and clean up may

only be done by authorised personnel.

Reference to other sections Refer to Section 8 and 13

SECTION 7. Handling and storage

Safe handling advice Wear personal protective equipment. Do not breathe vapours

or spray mist. Avoid contact with skin and eyes. Ensure adequate ventilation. Keep away from flames and sparks.

Advice on protection

No data available

against fire and explosion

Requirements for storage

Keep away from heat.Do not store near combustible materials.

areas and containers

Advice on common storage No data available

Print Date 26.06.2023 **100000006523** 5/12



Hydraulic Fluid 46

Version 1.01 Revision Date 26.06.2023

SECTION 8. Exposure controls/personal protection

Components with workplace control parameters

NATIONAL OCCUPATIONAL EXPOSURE LIMITS

Contains no substances with occupational exposure limit values.

Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Respiratory protection In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection Gloves suitable for permanent contact:

Material: butyl-rubber
Break through time: 4 h
Material thickness: 0.5 mm

Eye protection Safety goggles

Skin and body protection lightweight protective clothing

Hygiene measures Wash hands before breaks and immediately after handling the

product.

SECTION 9. Physical and chemical properties



Hydraulic Fluid 46

Version 1.01 Revision Date 26.06.2023

Information on basic physical and chemical properties

Form Liquid

State of matter Liquid; at 20 ° C; 1,013 hPa

Colour light brown

Odour mild

Odour Threshold No data available

pH No data available

Pour point -21 ° C

Flash point 225 ° C

Evaporation rate No data available

Flammability (solid, gas) No data available

Auto-ignition temperature > 320 ° C

Lower explosion limit No data available

Upper explosion limit No data available

Vapour pressure No data available

Relative vapour density No data available

Density 0.87 g/cm3; 20 $^{\circ}$ C

Water solubility immiscible

Partition coefficient: n-

No data available

octanol/water

Viscosity, kinematic 47 mm2/s; 40 ° C

SECTION 10. Stability and reactivity



Hydraulic Fluid 46

Version 1.01 Revision Date 26.06.2023

Reactivity Stable under normal conditions.

Chemical stability No data available

Possibility of hazardous

reactions

Strong acids and oxidizing agents

Conditions to avoid No data available

Materials to avoid Combustible material

Hazardous decomposition

products

Stable under normal conditions.

SECTION 11. Toxicological information

Acute oral toxicity Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

LD50 Rat: 5,000 mg/kg;

Acute inhalation toxicity Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

LC50 Rat: 4 h; 2.18 - 5.53 mg/l;

Acute dermal toxicity Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

LD50 Rabbit: 2,000 - 5,000 mg/kg;

Repeated dose toxicity Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

Oral Rat; Lowest observed adverse effect level 125 mg/kg

Print Date 26.06.2023 100000006523 8/12



Hydraulic Fluid 46

Version 1.01 Revision Date 26.06.2023

Repeated dose toxicity Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

Dermal Rat; NOAEL Early embryonic development 30 - 2,000

mg/kg

Repeated dose toxicity Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

Dermal Mouse; NOAEL Early embryonic development 150 mg/kg Lowest observed adverse effect level 100 mg/kg

Repeated dose toxicity Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

Dermal Rabbit; NOAEL Early embryonic development 1,000

mg/kg

Carcinogenicity Mineral oils are severely solvent refined or hydrotreated.

SECTION 12. Ecological information

Toxicity to fish Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

4 d; LL50; 100 mg/l;

Toxicity to daphnia and other

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

aquatic invertebrates

unspecified:

No data available

Toxicity to algae Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

unspecified:

No data available

Toxicity to bacteria Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil -

Print Date 26.06.2023 **100000006523** 9/12



Hydraulic Fluid 46

Version 1.01 Revision Date 26.06.2023

unspecified:

No data available

SECTION 13. Disposal considerations

Product Dispose of in accordance with local regulations.

SECTION 14. Transport information

Further Information Not classified as dangerous in the meaning of transport

regulations.

SECTION 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Canadian Domestic Substances List (DSL) Components Not listed

Mineral Oil

Alkyl Phenol (isomer)

Australian Inv. of Chem. Substances (AICS) Components Not listed

Mineral Oil

Alkyl Phenol (isomer)

New Zealand Inventory of Chemicals Components Not listed

(NZIoC) Mineral Oil

Alkyl Phenol (isomer)

Jap. Inv. of Exist. & New Chemicals (ENCS) Components Not listed

Distillates (petroleum), hydrotreated heavy paraffinic

Print Date 26.06.2023 100000006523 10/12



Hydraulic Fluid 46

Version 1.01 Revision Date 26.06.2023

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts

Mineral Oil

Alkyl Phenol (isomer)

Japan. Industrial Safety & Health Law (ISHL) Components Not listed

Distillates (petroleum), hydrotreated heavy paraffinic

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts

Mineral Oil

Alkyl Phenol (isomer)

Korea. Existing Chemicals Inventory (KECI) Components Not listed

Mineral Oil

Alkyl Phenol (isomer)

Philippines Inventory of Chemicals and

Chemical Substances (PICCS)

Components Not listed

Mineral Oil

Alkyl Phenol (isomer)

China Inv. Existing Chemical Substances

(IECSC)

Components Not listed

Mineral Oil

Alkyl Phenol (isomer)

Taiwan. Chemical Substances Inventory

(TCSI)

Components Not listed

Mineral Oil

Alkyl Phenol (isomer)

USA TSCA Inventory Components Not listed

Mineral Oil

Alkyl Phenol (isomer)

SECTION 16. Other information

Print Date 26.06.2023 **100000006523** 11/12



Hydraulic Fluid 46

Version 1.01

Revision Date 26.06.2023

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

All reasonable efforts were exercised to compile this SDS in accordance with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS). The SDS only provides information regarding the health, safety and environmental hazards at the date of issue, to facilitate the safe receipt, use and handling of this product in the workplace and does not replace any product information or product specifications. Since Sasol and its subsidiaries cannot anticipate or control all conditions under which this product may be handled, used and received in the workplace, it remains the obligation of each user, receiver or handler to, prior to usage, review this SDS in the context within which this product will be received, handled or used in the workplace. The user, handler or receiver must ensure that the necessary mitigating measures are in place with respect to health and safety. This does not substitute the need or requirement for any relevant risk assessments to be conducted. It further remains the responsibility of the receiver, handler or user to communicate such information to all relevant parties that may be involved in the receipt, use or handling of this product.

Although all reasonable efforts were exercised in the compilation of this SDS, Sasol does not expressly warrant the accuracy of, or assume any liability for incomplete information contained herein or any advice given. When this product is sold, risk passes to the purchaser in accordance with the specific terms and conditions of sale.

Print Date 26.06.2023 100000006523 12/12