

Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

SECTION 1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name Sabutol

Product code 2051

Relevant identified uses of the substance or mixture and uses advised against

Use Raw material for printing inks and printing ink additives. Paint related material

Uses advised against Prohibited for use in production of hand sanitizer.

Manufacturer or supplier's details

Company Sasol Chemicals, a division of Sasol South Africa (Pty) Ltd

Address Sasol Place, 50 Katherine Street
Sandton
2090
South Africa

Telephone +27103445000

E-mail address sasolchem.info.sa@sasol.com

Supplier's details Sasol Chemicals Pacific Ltd

61 Robinson Road
#17-02, 61 Robinson
Singapore

068893

Telephone +65 6533 8856

E-mail address info.sg@sasol.com

Emergency Phone Number

Emergency telephone number +44 (0)1235 239 670 (Europe, Israel, Africa, Americas)

+44(0)1235 239 671 (Middle East, Arabic African countries)

+65 3158 1074 (Asia Pacific)

Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

+86 400 120 6011 (China)
 +27 (0)17 610 4444 (South Africa)
 0800 112 890 RSA-Local only
 +61 (2) 8014 4558 (Australia)

SECTION 2. Hazards identification

Classification of the substance or mixture

GHS Classification

SS 586 : Part 2: Specification for Hazard Communication for Hazardous Chemicals and Dangerous Goods, Part 2 : Globally harmonized system of classification and labelling of chemicals - Singapore's adaptations

Classification

Flammable liquids	Category 3
Acute toxicity	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity - single exposure	Category 3

GHS label elements

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

H226 Flammable liquid and vapour.
 H302 Harmful if swallowed.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

:

Prevention:
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
 P233 Keep container tightly closed.

Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264+P265 Wash hands thoroughly after handling. Do not touch eyes.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P317 + P330 IF SWALLOWED: Get medical help. Rinse mouth.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P354 + P338 + P317 IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical help.
P317 Get medical help.
P321 Specific treatment (see supplemental first aid instructions on this label).
P332 + P317 If skin irritation occurs: Get medical help.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P403 + P233 + P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3. Composition/information on ingredients

HAZARDOUS INGREDIENTS

butan-1-ol

Contents: ≥ 60.00 % W/W

CAS-No. 71-36-3

Index-No. 603-004-00-6

EC-No. 200-751-6

Hazard statements H226 H302 H335 H315 H318 H336

pentan-2-ol

Contents: < 25.00 % W/W

CAS-No. 6032-29-7

Index-No. 603-006-00-7

EC-No. 227-907-6

Hazard statements NA

2-methylpropan-1-ol

Contents: < 20.00 % W/W

CAS-No. 78-83-1

Index-No. 603-108-00-1

EC-No. 201-148-0

Hazard statements H226 H315 H318 H335 H336

3-Methyl-2-butanol

Contents: < 10.00 % W/W

CAS-No. 598-75-4

Index-No. 603-006-00-7

EC-No. 209-950-2

Hazard statements NA

Pentan-3-ol

Contents: < 10.00 % W/W

CAS-No. 584-02-1

Index-No. 603-006-00-7

EC-No. 209-526-7

Hazard statements H226 H332 H335 H315



Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

propan-1-ol

Contents: < 5.00 % W/W

CAS-No. 71-23-8

Index-No. 603-003-00-0

EC-No. 200-746-9

Hazard statements *H226 H318 H336*

butan-2-ol

Contents: < 5.00 % W/W

CAS-No. 78-92-2

Index-No. 603-004-01-3

EC-No. 201-158-5

Hazard statements *H319 H335 H336 H226*

Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

SECTION 4. First aid measures

Description of necessary first-aid measures

Inhalation	Move to fresh air in case of accidental inhalation of vapours. In case of shortness of breath, give oxygen. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.
Skin contact	Wash off immediately with plenty of water for at least 15 minutes. Call a physician immediately.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Call a physician immediately.
Ingestion	If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed

Refer to SECTION 11

SECTION 5. Firefighting measures

Suitable extinguishing media	Water spray. Dry powder. Alcohol-resistant foam.
Special hazards arising from the substance or mixture	Flash back possible over considerable distance. Do not allow run-off from fire fighting to enter drains or water courses.
Special protective equipment for firefighters	Wear self-contained breathing apparatus and protective suit.

Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

SECTION 6. Accidental release measures

- Personal precautions** Use personal protective equipment. Do not breathe vapours or spray mist. Ensure adequate ventilation. Keep away from sources of ignition - No smoking. Use non-sparking tools. Shut off all sources of ignition.
- Environmental precautions** Avoid subsoil penetration. Do not flush into surface water or sanitary sewer system.
- Methods for cleaning up** Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). The material taken up must be disposed of in accordance with regulations.
- Reference to other sections** Refer to Section 8 and 13

SECTION 7. Handling and storage

- Safe handling advice** Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking. Provide sufficient air exchange and/or exhaust in work rooms. Take precautionary measures against static discharges. Ensure all equipment is electrically grounded before beginning transfer operations.
- Advice on protection against fire and explosion** Use explosion-proof equipment. Provide sufficient air exchange and/or exhaust in work rooms. Keep away from sources of ignition - No smoking.
- Requirements for storage areas and containers** Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.
- Advice on common storage** No data available

SECTION 8. Exposure controls/personal protection

Components with workplace control parameters

NATIONAL OCCUPATIONAL EXPOSURE LIMITS

Components	Type	Control parameters	Update	Basis

Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

N-BUTANOL	STEL	152 mg/m ³	2006	Singapore PELs
	STEL	50 ppm	2006	Singapore PELs
ISOBUTYL ALCOHOL	TWA	152 mg/m ³	2006	Singapore PELs
	TWA	50 ppm	2006	Singapore PELs
SEC-BUTANOL	TWA	303 mg/m ³	2006	Singapore PELs
	TWA	100 ppm	2006	Singapore PELs
N-PROPYL ALCOHOL N-PROPYL ALCOHOL	TWA	492 mg/m ³	2006	Singapore PELs
	TWA	200 ppm	2006	Singapore PELs
	STEL	614 mg/m ³	2006	Singapore PELs
	STEL	250 ppm	2006	Singapore PELs

Exposure controls

Engineering measures

Provide sufficient air exchange and/or exhaust in work rooms.

Personal protective equipment

Hand protection

Gloves suitable for permanent contact.:

Material: butyl-rubber

Break through time: 4 h

Material thickness: 0.5 mm

Eye protection

Safety glasses with side-shields

Skin and body protection

Protective suit. Safety shoes

Hygiene measures

Wash hands before breaks and immediately after handling the product.

SECTION 9. Physical and chemical properties

Information on basic physical and chemical properties

Form	Liquid
State of matter	Liquid; at 20 °C; 1,013 hPa
Colour	Colourless
Odour	Alcohol-like
Odour Threshold	No data available
pH	Not applicable

Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

Melting point/range	-89 °C
Boiling point/boiling range	117 °C
Flash point	35 °C; closed cup
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Auto-ignition temperature	No data available
Decomposition Temperature	No data available
Lower explosion limit	1.4 %(V)
Upper explosion limit	11.2 %(V)
Vapour pressure	No data available
Relative vapour density	No data available
Density	0.81 g/cm ³ ; 20 °C
Water solubility	partly soluble
Partition coefficient: n-octanol/water	No data available
Viscosity, kinematic	4.05 mm ² /s; 20 °C

SECTION 10. Stability and reactivity

Reactivity	Stable under recommended storage conditions.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Vapours may form explosive mixture with air.
Conditions to avoid	Heat, flames and sparks.
Materials to avoid	Oxidizing agents. Reducing agents Acids and bases
Hazardous decomposition products	Stable under recommended storage conditions.

SECTION 11. Toxicological information

Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

Acute oral toxicity	Acute toxicity estimate : 100 mg/kg; Calculation method;
Acute oral toxicity	butan-2-ol: LD50 Oral Rat: male 2,054 mg/kg; (literature value)
Acute oral toxicity	propan-1-ol: LD50 : > 5,000 mg/kg; OECD Test Guideline 401; (literature value) Based on available data, the classification criteria are not met.
Acute oral toxicity	butan-1-ol: LD50 Mouse: 2,290 mg/kg; OECD Test Guideline 401; GLP: no (literature value)
Acute oral toxicity	2-methylpropan-1-ol: LD50 Rat: female > 2,830 mg/kg; GLP: yes (literature value)
Acute inhalation toxicity	2-methylpropan-1-ol: LC0 Rat: male and female; 6 h; vapour; > 6000 ppm; OECD Test Guideline 403; GLP: yes; (literature value)
Acute inhalation toxicity	butan-1-ol: No adverse effect has been observed in acute toxicity tests.
Acute inhalation toxicity	propan-1-ol: LC50 Rat: 4 h; > 20 mg/l; OECD Test Guideline 403; (literature value), Based on available data, the classification criteria are not met.
Acute inhalation toxicity	butan-2-ol: LC50 Rat: male; 4 h; vapour; 16000 ppm; GLP: no; (literature value)
Acute dermal toxicity	butan-1-ol: LD50 Rabbit: male; 3,434 mg/kg; GLP: no; (literature value)
Acute dermal toxicity	2-methylpropan-1-ol: LD50 Rabbit: > 2,000 mg/kg; OECD Test Guideline 402; (literature value)
Acute dermal toxicity	propan-1-ol: LD50 Dermal Rabbit: > 2,000 - 5,000 mg/kg; OECD Test Guideline 402; (literature value), Based on available data, the classification criteria are not met.
Acute dermal toxicity	butan-2-ol: LD50 Dermal Rat: male and female; > 2,000 mg/kg; (literature value)
Skin irritation	propan-1-ol: Rabbit: No skin irritation; OECD Test Guideline 404 (literature

Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

	value)
Skin irritation	butan-1-ol: Rabbit: irritating; OECD Test Guideline 404 GLP: no; (literature value)
Skin irritation	2-methylpropan-1-ol: Rabbit: irritating; (literature value)
Eye irritation	butan-1-ol: Rabbit: irritating GLP: no; (literature value)
Eye irritation	2-methylpropan-1-ol: Rabbit: irritating (literature value)
Eye irritation	propan-1-ol: Rabbit: Risk of serious damage to eyes. Category 1; OECD Test Guideline 405 (literature value)
Eye irritation	butan-2-ol: Rabbit: irritating OECD Test Guideline 405 1 d; GLP: yes; (literature value)
Mutagenicity	propan-1-ol: In vitro tests did not show mutagenic effects; (literature value)
Mutagenicity	butan-1-ol: Ames test: Salmonella typhimurium; with and without; Not mutagenic; OECD Test Guideline 471; GLP: no; (literature value)
Mutagenicity	2-methylpropan-1-ol: Experiments showed mutagenic effects in cultured bacterial cells. Ames test: Salmonella typhimurium; with and without; Not mutagenic; (literature value)

SECTION 12. Ecological information

Toxicity to fish	propan-1-ol: semi-static test; Pimephales promelas (fathead minnow); 96 h; LC50; > 100 mg/l; OECD Test Guideline 203; (literature value)
-------------------------	---

Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

Toxicity to fish	butan-2-ol: static test; Pimephales promelas; 96 h; LC50; 2,993 mg/l; (literature value)
Toxicity to fish	butan-1-ol: flow-through test; Pimephales promelas; 96 h; LC50; 1,730 mg/l; GLP: no; (literature value)
Toxicity to fish	2-methylpropan-1-ol: flow-through test; Pimephales promelas; 96 h; LC50; 1,430 mg/l; (literature value)
Toxicity to daphnia and other aquatic invertebrates	2-methylpropan-1-ol: static test; Daphnia pulex (Water flea); 48 h; EC50; 1,100 mg/l(literature value)
Toxicity to daphnia and other aquatic invertebrates	butan-1-ol: static test; Daphnia magna; 48 h; EC50; 1,983 mg/IGLP: no; (literature value)
Toxicity to daphnia and other aquatic invertebrates	propan-1-ol: static test; Daphnia magna (Water flea); 48 h; EC50; > 100 mg/l(literature value)
Toxicity to daphnia and other aquatic invertebrates	butan-2-ol: static test; Daphnia magna (Water flea); 24 h; EC50; 2,300 mg/IGLP: no; (literature value)
Toxicity to bacteria	propan-1-ol: static test; 3 h; IC50; > 1,000 mg/l; ; activated sludge, domestic; (literature value)
Toxicity to bacteria	butan-2-ol: Pseudomonas putida; 16 h; 500 mg/IGLP: no; ; Information taken from reference works and the literature.
Toxicity to bacteria	butan-1-ol: Pseudomonas putida; 17 h; EC50; 4,390 mg/l; Information taken from reference works and the literature.
Toxicity to bacteria	2-methylpropan-1-ol: Pseudomonas putida; 16 h; 280 mg/l; Information taken from reference works and the literature.
Chronic toxicity in aquatic invertebrates	propan-1-ol: NOEC; Daphnia magna; ; 21 dEC50; 68.3 mg/l(reproduction rate; ; Fresh water; QSAR, (literature value)
Chronic toxicity in aquatic invertebrates	butan-1-ol: semi-static test; Daphnia magna; ; 21 d4.1 mg/l; (literature value)

Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

Chronic toxicity in aquatic invertebrates	2-methylpropan-1-ol: Daphnia magna; ; 21 d20 mg/l; Information taken from reference works and the literature.
Biodegradability	propan-1-ol: aerobic; 70 %; 20 d; Readily biodegradable.; OECD Guideline 301 D; (literature value)
Biodegradability	butan-2-ol: aerobic; 86 %; 5 d; GLP: no; (literature value)
Biodegradability	butan-1-ol: aerobic; activated sludge of a predominantly domestic sewage; 3 mg/l; 92 %; 20 d; Readily biodegradable.; GLP: no; (literature value)
Biodegradability	2-methylpropan-1-ol: aerobic; 100 mg/l; > 70 %; 14 d; Readily biodegradable.; OECD Guideline 301 A (new version); (literature value)

SECTION 13. Disposal considerations

Product	Disposal should be in accordance with local, regional and national legislations.
Packaging	Dispose of spent product packaging responsibly and lawfully with due consideration for health, safety and the environment.

SECTION 14. Transport information

DG Pictogram



ADR

UN number:	1987
Class:	3
Packaging group:	III; F1;
Proper shipping name:	ALCOHOLS, N.O.S.



Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

(butanols, pentanols)

RID

UN number: 1987
Class: 3
Packaging group: III; F1
Proper shipping name: ALCOHOLS, N.O.S.
(butanols, pentanols)

ADNR

UN number: 1987
Class: 3
Packaging group: III; F1
Proper shipping name: ALCOHOLS, N.O.S.
(butanols, pentanols)

IMDG

UN number: 1987
Class: 3
EmS: F-E, S-D
Packaging group: III
Proper shipping name: ALCOHOLS, N.O.S.
(butanols, pentanols)

Marine pollutant Not a Marine Pollutant

ICAO/IATA

UN number : 1987

Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

Class: 3

Packaging group: III

Proper shipping name: ALCOHOLS,N.O.S.
(butanols, pentanols)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Noxious liquid, N, F, (8) n.o.s (Sabutol, contains - n-propyl alcohol)
Ship Type: 3

POLLUTION CATEGORY: Y

SECTION 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Canada. DSL - Domestic Substances List, part of CEPA	All chemical constituents are listed in: Canada. DSL - Domestic Substances List, part of CEPA (See chapter 3)
Australia. AICS - Australian Inventory of Chemical Substances	All chemical constituents are listed in: Australia. AICS - Australian Inventory of Chemical Substances (See chapter 3)
New Zealand Inventory of Chemicals (NZIoC)	All chemical constituents are listed in: New Zealand Inventory of Chemicals (NZIoC) (See chapter 3)
Japan. ENCS - Existing and New Chemical Substances Inventory	All chemical constituents are listed in: Japan. ENCS - Existing and New Chemical Substances Inventory (See chapter 3)
Japan. Industrial Safety and Health Law - Inventory	All chemical constituents are listed in: Japan. Industrial Safety and Health Law - Inventory (See chapter 3)
Korea. KECI - Korean Existing Chemicals Inventory	All chemical constituents are listed in: Korea. KECI - Korean Existing Chemicals Inventory (See chapter 3)
Philippines. PICCS - Philippines Inventory of Chemicals and Chemical Substances	All chemical constituents are listed in: Philippines. PICCS - Philippines Inventory of Chemicals and Chemical Substances (See chapter 3)



Safety Data Sheet

Sabutol

Version 1.05

Revision Date 19.03.2025

China Inv. Existing Chemical Substances (IECSC)

Components Not listed

3-Methyl-2-butanol

Taiwan. Chemical Substances Inventory (TCSI)

All chemical constituents are listed in: Taiwan. Chemical Substances Inventory (TCSI) (See chapter 3)

USA TSCA Inventory

All chemical constituents are listed in: USA TSCA Inventory (See chapter 3)

SECTION 16. Other information

Full text of H-Statements

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

All reasonable efforts were exercised to compile this SDS in accordance with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS). The SDS only provides information regarding the health, safety and environmental hazards at the date of issue, to facilitate the safe receipt, use and handling of this product in the workplace and does not replace any product information or product specifications. Since Sasol and its subsidiaries cannot anticipate or control all conditions under which this product may be handled, used and received in the workplace, it remains the obligation of each user, receiver or handler to, prior to usage, review this SDS in the context within which this product will be received, handled or used in the workplace. The user, handler or receiver must ensure that the necessary mitigating measures are in place with respect to health and safety. This does not substitute the need or requirement for any relevant risk assessments to be conducted. It further remains the responsibility of the receiver, handler or user to communicate such information to all relevant parties that may be involved in the receipt, use or handling of this product.

Although all reasonable efforts were exercised in the compilation of this SDS, Sasol does not expressly warrant the accuracy of, or assume any liability for incomplete information contained herein or any advice given. When this product is sold, risk passes to the purchaser in accordance with the specific terms and conditions of sale.