



Description

Sasol Chemicals LPA Solvent is a high-purity mixture of hydrotreated isoparaffins and naphthenics with very low levels of polynuclear aromatics. It is a clear liquid with a medium flash point and mild odor.

Applications

Sasol Chemicals LPA Solvent may be used in a wide array of applications including pesticide formulations, consumer products, lubricating oils, chemical process solvents, degreasers, torch fuel, freeze point depressants and water treatment chemicals.

Properties

Typical physical properties are listed in the table to the right. Actual properties will vary from lot to lot.

Contact information

For technical information:

Product Steward

2201 Old Spanish Trail

Westlake, Louisiana 70669

Telephone: +1(337)494-4133

TDS.ProductSteward@us.sasol.com

For sales, pricing or samples,

contact a sales representative at:

Telephone: +1(281)588-3870

alkylates@us.sasol.com

Regulatory Compliance

If this material is used in a consumer product or in certain other specific applications, some exemptions may apply. Please contact a sales representative for more information on particular FDA regulations or for solvent status as an LVP-VOC for consumer products. This product is classified as non-regulated per DOT regulations.

Typical properties	Method	LPA Solvent
Distillation Range, °F		
IBP		350 – 370
10%	ASTM D-86	385 – 395
90%		465 – 475
95%		480 – 490
EP		390 – 540
Flash Point, (Tag CC) °C (°F)	ASTM D-56	> 60 (140)
Freeze Point, °C (°F)	ASTM D-2386	< -67 (-90)
Pour Point, °C (°F)	ASTM D-97	< -68 (-90)
Specific Gravity @ 16°C/60°F	ASTM D-287	0.80 - 0.82
Density, lbs/gal @ 16°C/60°F	ASTM D-287	6.68 – 6.84
Average Molecular Weight	API	172 – 176
Aromatic - BTEX, ppm	EPA 8260B	ND*
Color, Saybolt Universal	ASTM D-156	> 25
Relative Evaporative Rate (n-Butyl Acetate = 1)	ASTM D-3539	0.02
Vapor Pressure, torr @ 20°C/68°F	API, calc	0.16
Viscosity, cSt @ 20°C/68°F @ 40°C/104°F	ASTM D-445	2.3 – 2.4 1.3 – 1.6
Aniline Point, °C (°F)	ASTM D-611	70 (158)
Kauri-Butanol Value	ASTM D-1133	28 – 32
Bromine Number	ASTM D-1159	< 0.2
Nitrogen, ppm		< 1
Sulfur, ppm		< 1
Water, ppm	Karl-Fischer	< 50

* - detection limit 36 ppb

The preceding data is based on tests and experience, which Sasol Chemicals believes reliable, and is supplied for informational purposes only. Sasol Chemicals expressly disclaims any liability whatsoever for damage or injury which results from the use of the preceding data and nothing contained therein shall constitute a guarantee, warranty, or representation (including freedom from patent liability) by Sasol Chemicals with respect to the data, the product described, or its fitness for use for any specific purpose, even if that purpose is known to Sasol Chemicals. For detailed safety and handling information regarding these products, please refer to the respective Sasol Chemicals Safety Data Sheet. 07/16/19

Sasol Chemicals North America LLC

12120 Wickchester Lane, Houston, TX 77079-2990

Phone +1 (281)588-3000, info@us.sasol.com

www.sasolnorthamerica.com