



SASOL
reaching new frontiers

Butyl Glycol Ether

Product Specification - Version 9a

Specifications	Minimum	Maximum	Test Method
Purity (wt% - wet basis)	99.0		GC
Water (wt%)		0.1	ASTM D1364
Acidity as Acetic Acid (wt%)		0.010	ASTM D1613
Color (Pt-Co)		10	ASTM D5386/D1209
Appearance	Clear and bright		ASTM E2680

Further Properties:

Density @ 20C (g/ml)	0.899	0.901	ASTM D4052
Refractive Index (nD20)	1.419	1.420	ASTM D1218
Distillation range @ 101.3 kPa (degrees C)			ASTM D1078
Initial Boiling Point	168		
Dry Point		173	

Notes: The Sales Specification values are continuously checked, documented and stored within the scope of quality assurance.

Reason for revision:

Version 2a dated 7/20/06 GAT– New format.

Version 4a dated 12/25/06 GAT – Specification layout revised for posting on website.

Version 5a dated 6/13/08 GAT - Dry Point changed from 172C to 173C max.

Version 6a dated 1/16/12 GAT – Add Acidity as Acetic Acid and remove Acid Number

Version 7a dated 11/15/12 GAT – Appearance E2680

Version 8a dated 11/5/13 GAT – Purity wet basis, Color D5386/D1209

Version 9a dated 7/31/14 GAT – Sasol Chemicals (USA) LLC

Deactivated 5/31/18 GAT

Sasol Chemicals (USA) LLC

12120 Wickchester
Houston, TX 77079
Telephone: (+1) 281 588 3000
www.sasol.com